



# EZYFLEX® EI

## EPDM hose with stainless steel braid DN12



### Sanitary

Sanitary appliances



- ▶ **Composition:**
  - EPDM tube according to EN 681-1 type WB
  - AISI 304 stainless steel braid
  - Nickel-plated brass fittings
  - Stainless steel crimping bushings
- ▶ **Sealing:**
  - Flat gasket on flat seat
- ▶ **Standard lengths:**  
300, 500, 700, 1000 mm
- ▶ **Application:**  
Hot and cold water supply for sanitary appliances

- ▶ **Technical data**
- Maximum temperature **+90°C (peaks to +110°C)**
- Max operating pressure **16 bar**
- 12 x 18 mm (DN12)**
- Minimum bending radius **72 mm**

### CUSTOM OFFER

- ▶ Specific length: **150 mm to over 10,000 mm**  
*MOQ depending on the desired length*
- ▶ Customisable fittings: diameter, material, etc.
- ▶ Customisable packaging: contact us

### ▶ Assembled hoses / References & Configurations

Reference	Hose	Fitting 1 / Thread	Fitting 2 / Thread
EI12P2P2		1/2"	1/2"
EI12P2P4		Female 1/2"	Female 3/4"
EI12P4P4		3/4"	3/4"
EI12P2M2		1/2"	1/2"
EI12P4M2		Female 3/4"	Male 1/2"
EI12P4M4		3/4"	3/4"
EI12P2C2		1/2"	Angled 1/2"
EI12P4C4		3/4"	3/4"



IFT Groupe Omerin SAS  
Zone Industrielle - F 63600 Ambert  
Tel: +33 (0)4 73 82 32 33  
ift@omerin.com

[www.flexibles.com](http://www.flexibles.com)

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.