



EZYFLEX® PEXI

PEX hose with stainless steel braid DN12



Sanitary
Sanitary appliances
for the public sector
and hospitals



► **Composition:**

- PEX tube
- AISI 304 stainless steel braid
- Nickel-plated brass fittings
- Stainless steel crimping bushings

► **Sealing:**

- Flat gasket on flat seat

► **Standard lengths:**

300, 500, 700, 1000 mm

► **Application:**

Hot and cold water supply for public sector and hospitals

► **Technical data**



Maximum temperature
+90°C



Max operating pressure **10 bar**



12 x 18 mm (DN12)



Minimum bending radius **65 mm**

CUSTOM OFFER

- Specific length: **150 mm to over 10,000 mm**
MOQ depending on the desired length
- Customisable fittings: diameter, material, etc.
- Customisable packaging: contact us

► **Assembled hoses / References & Configurations**

| Reference | Hose | Fitting 1 / Thread | | Fitting 2 / Thread | |
|-----------|------|--------------------|------|--------------------|------|
| | | | | | |
| XI12P2P2 | | Female | 1/2" | Female | 1/2" |
| XI12P2P4 | | | 1/2" | | 3/4" |
| XI12P4P4 | | | 3/4" | | 3/4" |
| XI12P2M2 | | Female | 1/2" | Male | 1/2" |
| XI12P4M2 | | | 3/4" | | 1/2" |
| XI12P4M4 | | | 3/4" | | 3/4" |
| XI12P2C2 | | Female | 1/2" | Angled | 1/2" |
| XI12P4C4 | | | 3/4" | | 3/4" |



IFT Groupe Omerin SAS
Zone Industrielle - F 63600 Ambert
Tel: +33 (0)4 73 82 32 33
ift@omerin.com

www.flexibles.com

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.