



# EKOFLEX® BT

Butyl hose with textile braid DN15 to 26

## Heating Heat pumps



- ▶ **Composition:**
  - Butyl tube
  - Textile braid with double blue edging
  - Brass fittings (except nickel-plated brass elbow DN20 and 26)
  - Stainless steel crimping bushings
- ▶ **Sealing:**
  - Flat gasket on flat seat (optional)
- ▶ **Standard lengths:** 300, 500, 700, 1000 mm
- ▶ **Application:** Hot and cold water supply for heat pumps. Can be installed on mixed reversible installations

- ▶ **Technical data**
- Maximum temperature **+90°C (peaks to +110°C)**
- Max operating pressure **16 Bar (DN15)**  
**10 Bar (DN20 and 26)**  
**6 Bar (DN33 to 50)**
- 15 x 22 mm (DN15)**  
**20 x 28 mm (DN20)**  
**26 x 35 mm (DN26)**
- Oxygen barrier according to DIN 4726 prevents the formation of sludge, micro-organisms and algae

### CUSTOM OFFER

- ▶ Specific length: **150 mm to over 10,000 mm**  
*MOQ depending on the desired length*
- ▶ Customisable fittings: diameter, material, etc.
- ▶ Customisable packaging: contact us

### ▶ Assembled hoses / References & Configurations

Reference	DN (mm)	Hose	Fitting 1 Thread		Fitting 2 Thread		Bending radius (mm)
BT15P2M2	15		Female	1/2"	Male	1/2"	88
BT15P4M4				3/4"		3/4"	
BT20P4M4				3/4"		3/4"	
BT26P5M5				1"		1"	
BT15P2P2	15		Female	1/2"	Female	1/2"	88
BT15P4P4				3/4"		3/4"	
BT20P4P4				3/4"		3/4"	
BT26P5P5				1"		1"	
BT15P2C2	15		Female	1/2"	Angled	1/2"	88
BT15P4C4				3/4"		3/4"	
BT20P4C4				3/4"		3/4"	
BT26P5C5				1"		1"	

\*Female nickel-plated brass elbow fitting



IFT Groupe Omerin SAS  
Zone Industrielle - F 63600 Ambert  
Tel: +33 (0)4 73 82 32 33  
ift@omerin.com

[www.flexibles.com](http://www.flexibles.com)

The information provided on this data sheet is indicative and subject to change without notice. All hoses ordered must comply with IFT's installation recommendations, which can be viewed in its catalogue. IFT can under no circumstances be held liable for any incidents arising from inappropriate use, particularly in the case of installation not carried out in accordance with the rules of the trade and the standards in force. © Registered trademark of IFT. Drawings and photos are not contractually binding. Reproduction is prohibited without the prior consent of IFT.