



MC fitting

Male fixed tapered



► Composition:

- Brass or nickel-plated brass
- Gas thread according to ISO 7
- Other materials on request (nickel-plated brass, stainless steel, etc.)

► Packaging:

- In bags
- Other packaging types on request

► Assembly:

MC fittings can be used on our QUAL'IFT® hoses (according to the indications in the table below)

► Sealing:

Flat gasket on flat seat

► Application:

All low-pressure applications

ASSEMBLY

► IFT fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"

CUSTOM OFFER

► Contact us for all your specific requirements

► Fittings for your low-pressure applications / References & Compositions

Reference	For hose	Material	Thread		Diameter
	DN (mm)		mm	thumb	mm
MC080LAC	08	Brass	8 x 13	1/4"	6.2
MC081LAC			12 x 17	3/8"	
MC101NIC	10	Nickel-plated brass	12 x 17	3/8"	7
MC102LAC		Brass	15 x 21	1/2"	
MC121LAA	12	Brass	12 x 17	3/8"	9.5
MC122LAC			15 x 21	1/2"	
MC152LAC	15	Brass	15 x 21	1/2"	12.5
MC154LAC			20 x 27	3/4"	
MC204LAC	20	Brass	20 x 27	3/4"	17
MC205LAC			26 x 34	1"	
MC265LAC	26	Brass	26 x 34	1"	22
MC336LAA	33	Brass	33 x 42	1"1/4	28
MC407LAA	40	Brass	40 x 49	1"1/2	34.5
MC508LAA	50	Brass	50 x 60	2	44