



# UMSM fitting

## Male Male union with spherical-tapered seat



### ► Composition:

- Brass
- Gas thread according to ISO 228
- Other materials on request (nickel-plated brass, stainless steel, etc.)

### ► Packaging:

- In bags
- Other packaging types on request

### ► Assembly:

UMSM fittings can be used with spherical-tapered fittings: PSM, RCPS

### ► Sealing:

Metal / Metal (A thread)  
In the thread (B thread)

### ► Application:

All low-pressure applications

## ASSEMBLY

- **IFT** fittings must be assembled by scrupulously following the recommended rules and stages in paragraph "Recommendations for use"

## CUSTOM OFFER

- Contact us for all your specific requirements

### ► Fittings for your low-pressure applications / References & Compositions

Reference	Material	Male thread		Male thread spherical-tapered	
		mm	inches	mm	inches
UMSM01LAG	Brass	8 x 13	1/4"	12 x 17	3/8"
UMSM0LAG				8 x 13	1/4"
UMSM10LAG		12 x 17	3/8"	8 x 13	1/4"
UMSM12LAG				15 x 21	1/2"
UMSM1LAG				12 x 17	3/8"
UMSM21LAG		15 x 21	1/2"	12 x 17	3/8"
UMSM24LAG				20 x 27	3/4"
UMSM2LAG				15 x 21	1/2"
UMSM42LAG		20 x 27	3/4"	15 x 21	1/2"
UMSM4LAG				20 x 27	3/4"
UMSM5LAG		26 x 34	1"	26 x 34	1"
UMSM6LAG		33 x 42	1"1/4	33 x 42	1"1/4
UMSM7LAG		40 x 49	1"1/2	40 x 49	1"1/2
UMSM87LAG		50 x 60	2"	40 x 49	1"1/2
UMSM8LAG				50 x 60	2"