

HIGH TEMPERATURE WIRES & CABLES

UL & cUL approval

Changes in **UL 858** require home appliance wiring to comply with **VW-1 Flame rating**




- ▶ **SILIFLON®**
Fluoropolymer insulated wires



- ▶ **SILICABLE®**
Silicone insulated wires



- ▶ **SILICABLE®**
Silicone insulated wires with reinforcing braid



- ▶ **SILICABLE®**
Very high temperature wires with composite insulation



- ▶ **SILICABLE®**
Silicone sheathed cables

omerin
LES CABLES DE L'EXTREME

HIGH TEMPERATURE WIRES AND CABLES FOR THE GENERAL MARKET

FLUOROPOLYMER INSULATED WIRES

SILIFLON® 150°C & 250°C Fluoropolymer insulation UL & cUL approval

VW-1 cUL US



- 1 • Bare, tin-plated, nickel-plated or silver-plated copper core
- 2 • Insulation: Fluorinated polymer

Approvals - standards

- UL approval as per standard UL 758 - File no.: E101965
- cUL approval (CSA) as per standard C22.2 No. 210 - File no.: E101965
- "Horizontal flame test" as per UL approval
 - "FT1 flame rating" as per cUL approval
 - "VW-1 flame test" as per UL approval

Characteristics General

- Continuous operating temperatures: -90°C to +150°C, +200°C or +250°C (as per style no.)
- Excellent resistance to aggressive chemical environments
- Excellent resistance to humidity and UV
 - Excellent mechanical strength

Electrical

- Rated voltage: as per style no.
- Test voltage: 10 x Rated voltage

Standard products

- All colours including two-coloured
- Stranding of conducting cores: contact us

KEY

Conducting metals

- B : Tin-plated copper
- B* Tin-plated copper (ø > 0.38 mm)
- C Nickel-plated copper
- D Silver-plated copper
- E Nickel
- F Bare copper
- F* Bare copper (ø > 0.38 mm)
- G Nickel-plated copper 27 %

AWM I A/B : Internal wiring

* The diameter is provided for information purposes as it may vary depending on the stranding of the core. Only the average thickness of insulation should be taken into account

Style n°	Insulation	10126-VW-1		1333-VW-1		1332-VW-1		1330-VW-1		1727-VW-1	
		ETFE "Thin wall"		FEP		FEP "Thick wall"		FEP "Thick wall"		PFA	
Approval	Nominal cross-section	AWM I A/B		AWM I A/B		AWM I A/B		AWM I A/B		AWM I A/B	
		150°C - 600 V		150°C - 300 V		200°C - 300 V		200°C - 600 V		250°C - 600 V	
AWG	(mm²)	Average thickness of insulation (mm)	Nominal diameter (mm)*	Average thickness of insulation (mm)	Nominal diameter (mm)*	Average thickness of insulation (mm)	Nominal diameter (mm)*	Average thickness of insulation (mm)	Nominal diameter (mm)*	Average thickness of insulation (mm)	Nominal diameter (mm)*
30	0.05	0.25	0.8	0.33	0.95	0.33	0.95	0.51	1.3	0.51	1.3
28	0.09	0.25	0.9	0.33	1.05	0.33	1.05	0.51	1.4	0.51	1.4
26	0.13	0.25	1.05	0.33	1.15	0.33	1.15	0.51	1.5	0.51	1.5
24	0.22	0.25	1.15	0.33	1.3	0.33	1.3	0.51	1.65	0.51	1.65
22	0.34	0.25	1.3	0.33	1.4	0.33	1.45	0.51	1.85	0.51	1.8
-	0.5	0.25	1.4	0.33	1.6	0.33	1.55	0.51	1.95	0.51	1.95
20	0.6	0.25	1.5	0.33	1.65	0.33	1.7	0.51	2.0	0.51	2.0
-	0.75	0.25	1.55	0.33	1.75	0.33	1.75	0.51	2.1	0.51	2.1
18	0.93	0.25	1.8	0.33	1.9	0.33	1.9	0.51	2.25	0.51	2.2
-	1	0.25	1.8	0.33	1.95	0.33	1.95	0.51	2.3	0.51	2.3
16	1.34	0.25	2.0	0.33	2.2	0.33	2.1	0.51	2.5	0.51	2.45
-	1.5	0.25	2.0	0.33	2.2	0.33	2.2	0.51	2.55	0.51	2.65
14	-	0.25	2.4	0.33	2.55	0.33	2.7	0.51	3.0	0.51	2.85
-	2.5	0.25	2.45	0.33	2.7	0.33	2.7	0.51	3.0	0.51	3.0
12	-	0.38	3.2	0.33	3.1	0.33	3.2	0.51	3.4	0.51	3.4
-	4	0.38	3.35	0.33	3.25	0.33	3.25	0.51	3.6	0.51	3.6
10	-	0.38	4.1	0.33	3.7	0.33	3.9	0.51	4.0	0.51	4.2
-	6	0.38	4.5	0.33	3.9	0.33	3.9	0.51	4.3	0.51	4.3
8	-	0.64	5.4	-	-	-	-	0.76	5.3	0.76	5.7
-	10	0.64	5.7	-	-	-	-	0.76	5.9	0.76	5.9
6	-	0.64	6.6	-	-	-	-	0.76	6.8	0.76	6.8
-	16	0.64	6.7	-	-	-	-	0.76	7.1	0.76	7.1
4	-	0.64	7.8	-	-	-	-	0.76	8.0	0.76	8.0
-	25	0.64	8.3	-	-	-	-	0.76	8.5	0.76	8.5
2	35	0.89	10.0	-	-	-	-	0.76	9.2	0.76	9.6
1	-	0.89	11.0	-	-	-	-	1.14	11.2	1.14	11.2
-	50	0.89	11.4	-	-	-	-	1.14	12.0	1.14	12.0
1/0	-	1.14	12.5	-	-	-	-	1.14	12.5	1.14	12.5
2/0	70	1.14	14.0	-	-	-	-	1.14	14.0	1.14	14.0
3/0	-	1.14	15.2	-	-	-	-	1.14	15.2	1.14	15.2
-	95	1.14	15.4	-	-	-	-	1.14	15.4	1.14	15.4
4/0	-	1.14	16.8	-	-	-	-	1.14	16.8	1.14	16.8
-	120	1.14	17.1	-	-	-	-	1.14	17.1	1.14	17.1
Conducting metals		BCDEFG		BCDEFG		B*CDEF*G		B*CDEF*G		CEG	

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert FRANCE

Phone: +33 (0)4 73 82 50 00

omerin@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. ® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

**HIGH TEMPERATURE WIRES AND CABLES
FOR THE GENERAL MARKET**

SILICONE INSULATED WIRES

**SILICABLE® 150°C
& 200°C**

**Silicone insulation
UL & cUL approval**

VW-1 cUL US



Approvals - standards

- UL approval as per standard UL 758 - File no.: E101965
 - cUL approval as per standard C22.2 No. 210 - File no.: E101965 (except for style no. 3132)
 - "Horizontal flame test" as per UL approval
 - "FT2 flame rating" as per cUL approval
 - "FT1 flame rating" as per cUL approval
 - "VW-1 flame test" as per UL approval

- 1 • Bare, tin-plated, nickel-plated or silver-plated copper core
- 2 • Insulation: Silicone rubber

**Characteristics
General**

- Continuous operating temperatures: -60°C to +150°C, +200°C (as per style no.)
- Good resistance to thermal shock and UV
- Halogen free (IEC 60754-1)

Electrical

- Rated voltage: as per style no.
- Test voltage: 10 x Rated voltage

Standard products

- Stranding of conducting cores: contact us
 - Up to 120 mm²: all colours including two-coloured.
 - From 150 mm² to 400 mm²: all colours except two-coloured.

Option

- CSA approval as per standard C22.2 No. 210 - File no.: LL84986 (only for style no. 3132) : contact us

KEY

Conducting metals

- B : Tin-plated copper
- B* Tin-plated copper (ø > 0.38 mm)
- C Nickel-plated copper
- D Silver-plated copper
- E Nickel
- F Bare copper
- F* Bare copper (ø > 0.38 mm)
- G Nickel-plated copper 27 %

AWM I A : Internal wiring
AWM I A/B : Internal wiring
not subjected to mechanical abuse

Not cUL approved

*The diameter is provided for information purposes as it may vary depending on the stranding of the core. Only the average thickness of insulation should be taken into account

For this product, please contact:

OMERIN division principale
Zone Industrielle – F 63600 Ambert FRANCE
Phone: +33 (0)4 73 82 50 00
omerin@omerin.com

Style n°		3132-VW-1		3134-VW-1		3135-VW-1		3512-VW-1	
Insulation		Silicone		Silicone		Silicone		Silicone	
Approval		150°C – 300 V		150°C – 600 V		200°C – 600 V		200°C – 600 V	
Nominal cross-section		Average thickness of insulation	Nominal diameter	Average thickness of insulation	Nominal diameter	Average thickness of insulation	Nominal diameter	Average thickness of insulation	Nominal diameter
AWG	(mm ²)	(mm)	(mm)*	(mm)	(mm)*	(mm)	(mm)*	(mm)	(mm)*
-	0.5	0.38	1.7	-	-	0.76	2.5	0.76	2.5
20	0.6	0.38	1.75	-	-	0.76	2.6	0.76	2.6
-	0.75	0.38	1.9	-	-	0.76	2.65	0.76	2.65
18	0.93	0.38	2.0	0.76	2.7	0.76	2.7	0.76	2.7
-	1	0.38	2.1	0.76	2.9	0.76	2.8	0.76	2.8
16	1.34	0.38	2.3	0.76	3.1	0.76	3.05	0.76	3.05
-	1.5	0.38	2.4	0.76	3.2	0.76	3.2	0.76	3.1
14	-	0.38	2.65	0.76	3.6	0.76	3.6	0.76	3.6
-	2.5	0.38	2.8	0.76	3.6	0.76	3.6	0.76	3.6
12	-	0.38	3.2	0.76	4.0	0.76	4.0	0.76	4.0
-	4	0.38	3.4	0.76	4.2	0.76	4.4	0.76	4.4
10	-	0.38	3.8	-	-	-	-	1.14	5.3
-	6	0.38	3.9	-	-	-	-	1.14	5.5
8	-	0.38	4.6	-	-	-	-	1.14	6.1
-	10	0.38	5.2	-	-	-	-	1.52	7.4
6	-	0.38	5.9	-	-	-	-	1.52	8.3
-	16	0.38	6.3	-	-	-	-	1.52	8.9
4	-	0.38	7.3	-	-	-	-	1.52	9.8
-	25	0.38	7.8	-	-	-	-	1.52	10.2
2	35	0.38	8.9	-	-	-	-	1.52	11.0
1	-	0.38	10.1	-	-	-	-	1.52	13.5
-	50	0.38	10.5	-	-	-	-	2.03	14.0
1/0	-	0.38	11.2	-	-	-	-	2.03	14.6
2/0	70	0.38	12.3	-	-	-	-	2.03	16.0
3/0	-	0.38	13.9	-	-	-	-	2.03	17.8
-	95	0.38	14.1	-	-	-	-	2.03	18.4
4/0	-	0.38	15.5	-	-	-	-	2.41	20.0
-	120	0.38	15.8	-	-	-	-	2.41	20.8
250MCM	-	-	-	-	-	-	-	2.41	21.4
-	150	-	-	-	-	-	-	2.41	22.3
300MCM	-	-	-	-	-	-	-	2.41	23.1
350MCM	185	-	-	-	-	-	-	2.41	24.0
400MCM	-	-	-	-	-	-	-	2.41	25.3
-	240	-	-	-	-	-	-	2.41	26.3
Conducting metals		BCDEFG		BCDEG		B*CDEF*G		B*CDEG	



www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. ® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

SILICABLE® 200°C

**Silicone insulation
with fiberglass braid
UL approval**

VW-1 



- 1 • Bare, tin-plated, nickel-plated or silver-plated copper core
- 2 • Insulation: Silicone rubber
- 3 • Coated fiberglass braid

Approvals - standards

- UL approval as per standard UL 758 - File no.: E101965
 - "Horizontal flame test" as per UL approval
 - "VW-1 flame test" as per UL approval

Characteristics General

- Continuous operating temperatures: -60°C to +200°C
- Good resistance to thermal shock and UV
 - Halogen free (IEC 60754-1)

Electrical

- Rated voltage: as per style no.
- Test voltage: 10 x Rated voltage

Standard products

- Stranding of conducting cores: contact us
- All colours with or without coloured spiral stripe

Option

- CSA approval as per standard C22.2 No. 210 - File no.: LL84986: contact us

KEY

Conducting metals

- B : Tin-plated copper
- B* Tin-plated copper (ø > 0,38 mm)
- C Nickel-plated copper
- D Silver-plated copper
- E Nickel
- F Bare copper
- F* Bare copper (ø > 0,38 mm)
- G Nickel-plated copper 27 %

AWM I A : Internal wiring
AWM I A/B : Internal wiring
not subjected to mechanical abuse

*The diameter is provided for information purposes as it may vary depending on the stranding of the core. Only the average thickness of insulation should be taken into account

For this product, please contact:

OMERIN division principale
Zone Industrielle – F 63600 Ambert FRANCE
Phone: +33 (0)4 73 82 50 00
omerin@omerin.com

OMERIN
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. ® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

Style n°	With reinforcing braid					
	Insulation	3122-VW-1 Silicone		3513-VW-1 Silicone		
		200°C – 300 V		200°C – 600 V		
Approval	Nominal cross-section	Average thickness of insulation	Nominal diameter	Average thickness of insulation	Nominal diameter	
AWG	(mm ²)	(mm)	(mm)*	(mm)	(mm)*	
-	0.5	0.38	2.0	0.76	2.8	
20	0.6	0.38	2.1	0.76	2.9	
-	0.75	0.38	2.2	0.76	3.0	
18	0.93	0.38	2.3	0.76	3.1	
-	1	0.38	2.4	0.76	3.2	
16	1.34	0.38	2.6	0.76	3.6	
-	1.5	0.38	2.7	0.76	3.7	
14	-	-	-	0.76	4.0	
-	2.5	-	-	0.76	4.1	
12	-	-	-	0.76	4.5	
-	4	-	-	0.76	4.7	
10	-	-	-	1.14	5.8	
-	6	-	-	1.14	6.0	
8	-	-	-	1.14	6.6	
-	10	-	-	1.52	8.0	
6	-	-	-	1.52	8.9	
-	16	-	-	1.52	9.5	
4	-	-	-	1.52	10.7	
-	25	-	-	1.52	11.1	
2	35	-	-	1.52	11.9	
1	-	-	-	1.52	14.4	
-	50	-	-	2.03	15.1	
1/0	-	-	-	2.03	15.6	
2/0	70	-	-	2.03	16.5	
3/0	-	-	-	2.03	18.2	
-	95	-	-	2.03	18.4	
4/0	-	-	-	2.41	20.5	
-	120	-	-	2.41	20.9	
250MCM	-	-	-	2.41	21.7	
-	150	-	-	2.41	22.4	
300MCM	-	-	-	2.41	23.6	
350MCM	185	-	-	2.41	24.6	
400MCM	-	-	-	2.41	25.6	
-	240	-	-	2.41	26.9	
Conducting metals		B*CDEF*G		B*CD		

SILICABLE® 350°C

Composite insulation
UL & cUL approval

VW-1 cUL US



- 1 • Nickel or nickel-plated copper core
- 2 • Composite insulation: Mica tape(s) and fibreglass lapping + varnished fibreglass braid

Approvals - standards

- UL approval as per standard UL 758 - File no.: E101965
- cUL approval (CSA) as per standard C22.2 No. 210 - File no.: E101965
 - "Horizontal flame test" as per UL approval
 - "FT1 flame rating" as per cUL approval
 - "VW-1 flame test" as per UL approval

Characteristics General

- Maximum continuous operating temperature: +350 °C
 - Good resistance to thermal shocks and oxidation

Electrical

- Rated voltage: as per style no.
- Test voltage: 10 x Rated voltage

Standard products

- Standard colours: grey, brown or natural. (other colours: contact us)
- Stranding of conducting cores: contact us

KEY

Conducting metals

- B : Tin-plated copper
- B* Tin-plated copper ($\phi > 0.38$ mm)
- C Nickel-plated copper
- D Silver-plated copper
- E Nickel
- F Bare copper
- F* Bare copper ($\phi > 0.38$ mm)
- G Nickel-plated copper 27 %

AWM I A/B : Internal wiring

Not cUL approved

* The diameter is provided for information purposes as it may vary depending on the stranding of the core. Only the average thickness of insulation should be taken into account

Style n°

Insulation

5304-VW-1

Composite

Approval

Nominal cross-section

AWM I A/B

350°C – 600 V

Average thickness of insulation

Nominal diameter

AWG	(mm ²)	(mm)	(mm)*
24	0.22	0.66	2.5
22	0.34	0.66	2.6
-	0.5	0.66	2.8
20	0.6	0.66	2.9
-	0.75	0.66	3.0
18	0.93	0.66	3.1
-	1	0.66	3.2
16	1.34	0.66	3.4
-	1.5	0.66	3.5
14	-	0.66	3.8
-	2.5	0.66	4.1
12	-	0.66	4.6
-	4	0.66	4.7
10	-	0.66	4.8

Conducting metals

EG

For this product, please contact:

OMERIN division principale

Zone Industrielle – F 63600 Ambert FRANCE

Phone: +33 (0)4 73 82 50 00

omerin@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. ® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

**HIGH TEMPERATURE WIRES AND CABLES
FOR THE GENERAL MARKET**

**SILICABLE® 150°C
& 200°C**
Silicone sheathing
UL & cUL approval



SILICONE SHEATED CABLES



- 1 • UL and cUL approved conductors with a silicone or fluoropolymer insulation (see table below for more information).
- 2 • Outer sheath: Silicone rubber.

Approvals - standards

- UL approval as per standard UL 758 - File no.: E101965
- cUL approval (CSA) as per standard C22.2 No. 210 - File no.: E101965 (LL84986)
- "Horizontal flame test" as per UL approval
 - "FT1 flame rating" as per cUL approval
 - "FT2 flame rating" as per cUL approval
 - "VW-1 flame test" as per UL approval

Characteristics

General

- Continuous operating temperatures: -60°C to +150°C, +200°C (as per style no.)
- Good resistance to thermal shock and UV

Electrical

- Rated voltage: 600 V
- Test voltage: 6 000 V

Standard products

- Standard outer sheath colours: black with or without coloured spiral stripe
- Stranding of conducting cores: contact us

Style n°

Insulation

4389-S150-VW-1

Silicone

4389-S200-VW-1

Silicone

4389-E150-VW-1

ETFE

Nb. of cond	Approval		AWM II A/B (Wall 1.14 mm) 150°C		AWM II A/B (Wall 1.14 mm) 200°C		AWM II A/B (Wall 1.14 mm) 150°C	
	Nominal cross-section	Nominal diameter of the cond. (mm)	Nominal diameter of the cond. (mm)*	Nominal diameter of the cond. (mm)	Nominal diameter of the cond. (mm)*	Nominal diameter of the cond. (mm)	Nominal diameter of the cond. (mm)*	
								AWG
2	26	0.13	-	-	-	-	1.05	4.3
3	26	0.13	-	-	-	-	1.05	4.5
4	26	0.13	-	-	-	-	1.05	4.8
5	26	0.13	-	-	-	-	1.05	5.1
7	26	0.13	-	-	-	-	1.05	5.4
2	24	0.22	-	-	-	-	1.15	4.5
3	24	0.22	-	-	-	-	1.15	4.7
4	24	0.22	-	-	-	-	1.15	5.0
5	24	0.22	-	-	-	-	1.15	5.3
7	24	0.22	-	-	-	-	1.15	5.7
2	22	0.34	-	-	-	-	1.3	4.8
3	22	0.34	-	-	-	-	1.3	5.1
4	22	0.34	-	-	-	-	1.3	5.4
5	22	0.34	-	-	-	-	1.3	5.8
7	22	0.34	-	-	-	-	1.3	6.2
2	-	0.5	2.5	7.2	2.5	7.2	1.4	5.0
3	-	0.5	2.5	7.6	2.5	7.6	1.4	5.3
4	-	0.5	2.5	8.3	2.5	8.3	1.4	5.6
5	-	0.5	2.5	9.0	2.5	9.0	1.4	6.0
7	-	0.5	2.5	9.7	2.5	9.7	1.4	6.4
2	20	0.6	2.5	7.2	2.6	7.4	1.5	5.2
3	20	0.6	2.5	7.8	2.6	7.9	1.5	5.5
4	20	0.6	2.5	8.3	2.6	8.5	1.5	5.9
5	20	0.6	2.5	9.0	2.6	9.3	1.5	6.3
7	20	0.6	2.5	9.7	2.6	10.0	1.5	6.7
2	-	0.75	2.7	7.6	2.65	7.5	1.55	5.3
3	-	0.75	2.7	8.1	2.65	8.0	1.55	5.6
4	-	0.75	2.7	8.7	2.65	8.6	1.55	6.0
5	-	0.75	2.7	9.5	2.65	9.4	1.55	6.4
7	-	0.75	2.7	10.3	2.65	10.2	1.55	6.9
2	18	0.93	2.8	7.8	2.7	7.6	1.8	5.8
3	18	0.93	2.8	8.3	2.7	8.1	1.8	6.1
4	18	0.93	2.8	9.0	2.7	8.7	1.8	6.6
5	18	0.93	2.8	9.8	2.7	9.5	1.8	7.1
7	18	0.93	2.8	10.6	2.7	10.3	1.8	7.6
2	-	1	2.9	8.0	2.8	7.8	1.8	5.8
3	-	1	2.9	8.5	2.8	8.3	1.8	6.1
4	-	1	2.9	9.2	2.8	9.0	1.8	6.6
5	-	1	2.9	10.1	2.8	9.8	1.8	7.1
7	-	1	2.9	10.9	2.8	10.6	1.8	7.6
2	16	1.34	3.1	8.4	3.05	8.3	2.0	6.2
3	16	1.34	3.1	8.9	3.05	8.8	2.0	6.6
4	16	1.34	3.1	9.7	3.05	9.6	2.0	7.1
5	16	1.34	3.1	10.6	3.05	10.5	2.0	7.6
7	16	1.34	3.1	11.5	3.05	11.4	2.0	8.2
2	-	1.5	3.2	8.6	3.1	8.4	2.0	6.2
3	-	1.5	3.2	9.2	3.1	8.9	2.0	6.6
4	-	1.5	3.2	10.0	3.1	9.7	2.0	7.1
5	-	1.5	3.2	10.9	3.1	10.6	2.0	7.6
7	-	1.5	3.2	11.8	3.1	11.5	2.0	8.2
2	14	-	3.4	9.0	3.6	9.4	2.4	7.0
3	14	-	3.4	9.6	3.6	10.0	2.4	7.4
4	14	-	3.4	10.4	3.6	10.9	2.4	8.0
5	14	-	3.4	11.4	3.6	12.0	2.4	8.7
7	14	-	3.4	12.4	3.6	13.0	2.4	9.4

Conducting metals

BCDEFG

B*CDEF*G

BCDEFG

SILICABLE® 150°C & 200°C

Silicone sheathing
UL & cUL approval

SILICONE SHEATED CABLES

Nb. of cond	Style n°		4389-E150-VW-1		4389-F200-VW-1		4389-F200-VW-1		4389-F200-VW-1	
	Insulation		ETFE "Thin wall"		ETFE "Thin wall"		ETFE "Thin wall"		FEP	
	Approval		AWM II A/B (Wall 1.14 mm)		AWM II A/B (Wall 1.14 mm)		AWM II A/B (Wall 1.14 mm)		AWM II A/B (Wall 1.14 mm)	
	Nominal cross-section		150°C		200°C		200°C		200°C	
	AWG	(mm²)	Nominal diameter of the cond. (mm)	Nominal diameter (mm)*	Nominal diameter (mm)	Nominal diameter (mm)*	Nominal diameter (mm)	Nominal diameter (mm)*	Nominal diameter of the cond. (mm)	Nominal diameter (mm)*
2	26	0.13	-	-	1.0	4.2	0.9	4.0	1.2	4.6
3	26	0.13	-	-	1.0	4.4	0.9	4.2	1.2	4.8
4	26	0.13	-	-	1.0	4.7	0.9	4.4	1.2	5.1
5	26	0.13	-	-	1.0	4.9	0.9	4.7	1.2	5.5
7	26	0.13	-	-	1.0	5.2	0.9	4.9	1.2	5.8
2	24	0.22	0.9	4.0	1.1	4.4	1.0	4.2	1.35	4.9
3	24	0.22	0.9	4.2	1.1	4.6	1.0	4.4	1.35	5.2
4	24	0.22	0.9	4.4	1.1	4.9	1.0	4.7	1.35	5.5
5	24	0.22	0.9	4.7	1.1	5.2	1.0	4.9	1.35	5.9
7	24	0.22	0.9	5.0	1.1	5.5	1.0	5.2	1.35	6.3
2	22	0.34	1.05	4.3	1.25	4.7	1.15	4.5	1.45	5.1
3	22	0.34	1.05	4.5	1.25	4.9	1.15	4.7	1.45	5.4
4	22	0.34	1.05	4.8	1.25	5.3	1.15	5.0	1.45	5.7
5	22	0.34	1.05	5.1	1.25	5.6	1.15	5.3	1.45	6.2
7	22	0.34	1.05	5.4	1.25	6.0	1.15	5.7	1.45	6.6
2	-	0.5	1.25	4.7	1.4	5.0	1.3	4.8	1.65	5.5
3	-	0.5	1.25	4.9	1.4	5.3	1.3	5.0	1.65	5.8
4	-	0.5	1.25	5.3	1.4	5.6	1.3	5.4	1.65	6.2
5	-	0.5	1.25	5.6	1.4	6.0	1.3	5.8	1.65	6.7
7	-	0.5	1.25	6.0	1.4	6.4	1.3	6.1	1.65	7.2
2	20	0.6	1.35	4.9	1.5	5.2	1.4	5.0	1.7	5.6
3	20	0.6	1.35	5.2	1.5	5.5	1.4	5.3	1.7	5.9
4	20	0.6	1.35	5.5	1.5	5.9	1.4	5.6	1.7	6.3
5	20	0.6	1.35	5.9	1.5	6.3	1.4	6.0	1.7	6.8
7	20	0.6	1.35	6.3	1.5	6.7	1.4	6.4	1.7	7.3
2	-	0.75	1.4	5.0	1.55	5.3	1.75	5.7	1.8	5.8
3	-	0.75	1.4	5.3	1.55	5.6	1.75	6.0	1.8	6.1
4	-	0.75	1.4	5.6	1.55	6.0	1.75	6.5	1.8	6.6
5	-	0.75	1.4	6.0	1.55	6.4	1.75	7.0	1.8	7.1
7	-	0.75	1.4	6.4	1.55	6.9	1.75	6.9	1.8	7.6
2	18	0.93	1.55	5.3	1.8	5.8	1.9	6.0	2.0	6.2
3	18	0.93	1.55	5.6	1.8	6.1	1.9	6.3	2.0	6.6
4	18	0.93	1.55	6.0	1.8	6.6	1.9	6.8	2.0	7.1
5	18	0.93	1.55	6.4	1.8	7.1	1.9	7.4	2.0	7.6
7	18	0.93	1.55	6.9	1.8	7.6	1.9	7.9	2.0	8.2
2	-	1	1.65	5.5	1.8	5.8	1.95	6.1	2.0	6.2
3	-	1	1.65	5.8	1.8	6.1	1.95	6.5	2.0	6.6
4	-	1	1.65	6.2	1.8	6.6	1.95	6.9	2.0	7.1
5	-	1	1.65	6.7	1.8	7.1	1.95	7.5	2.0	7.6
7	-	1	1.65	7.2	1.8	7.6	1.95	8.1	2.0	8.2
2	16	1.34	1.9	6.0	2.0	6.2	2.2	6.6	2.2	6.6
3	16	1.34	1.9	6.3	2.0	6.6	2.2	7.0	2.2	7.0
4	16	1.34	1.9	6.8	2.0	7.1	2.2	7.5	2.2	7.5
5	16	1.34	1.9	7.4	2.0	7.6	2.2	8.2	2.2	8.2
7	16	1.34	1.9	7.9	2.0	8.2	2.2	8.8	2.2	8.8
2	-	1.5	1.9	6.0	2.0	6.2	2.0	6.8	2.3	6.8
3	-	1.5	1.9	6.3	2.0	6.6	2.2	7.2	2.3	7.2
4	-	1.5	1.9	6.8	2.0	7.1	2.2	7.8	2.3	7.8
5	-	1.5	1.9	7.4	2.0	7.6	2.2	8.5	2.3	8.5
7	-	1.5	1.9	7.9	2.0	8.2	2.2	9.1	2.3	9.1
2	14	-	2.25	6.7	2.4	7.0	2.6	7.4	2.6	7.4
3	14	-	2.25	7.1	2.4	7.4	2.6	7.9	2.6	7.9
4	14	-	2.25	7.7	2.4	8.0	2.6	8.5	2.6	8.5
5	14	-	2.25	8.3	2.4	8.7	2.6	9.3	2.6	9.3
7	14	-	2.25	9.0	2.4	9.4	2.6	10.0	2.6	10.0

Conducting metals

BCDEFG

B*CDEF*G

B*CDEF*G

B*CDEF*G

KEY

Conducting metals

- B Tin-plated copper
- B* Tin-plated copper (ø > 0.38 mm)
- C Nickel-plated copper
- D Silver-plated copper
- E Nickel
- F Bare copper
- F* Bare copper (ø > 0.38 mm)
- G Nickel-plated copper 27 %

AWM II A/B : External or
Internal wiring

*The diameter is provided for information purposes as it may vary depending on the stranding of the core. Only the average thickness of insulation should be taken into account

For this product, please contact:

OMERIN division principale

Zone Industrielle – F 63600 Ambert FRANCE

Phone: +33 (0)4 73 82 50 00

omerin@omerin.com

OMERIN
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. ® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.