

HIGH TEMPERATURE MEDIUM VOLTAGE
POWER CABLES**SILICOU[®]**
Style 3663 - 7.2 kVUL approval
-60 °C to +180 °C**Approvals - standards**


- UL approval (180 °C / 7200 V) as per standard UL 758 – File no.: E101965.
- • Compliance with the tests described as per standard IEC 60092-350/354/360, IEC 60331-11/21, IEC 60332-1-1/2, IEC 60332-3-22 category A and IEC 60754-2.
 - Horizontal flame as per UL approval.

Applications

- Cabling for rotating machines: motors, alternators, generators.
- Cabling for static machines: transformers, inductors, inverters, choppers.
- Shipbuilding and railway construction.
 - Power cabinets.

Options

- Flexible bare copper core - class 5 as per IEC 60228: contact us.
- • Flexible or extra-flexible silver-plated or nickel-plated copper core - class 5 or 6 as per IEC 60228: contact us.
 - Without reinforcing braid: contact us.
- Varnished synthetic fibre reinforcing braid: contact us.
- Very high temperature fibre reinforcing braid: contact us.
- • Multi-conductor cable made up of an assembly of several single conductor cables SILICOU[®] Style 3663 7.2 KV: contact us.
 - Other colours: contact us.
- Other nominal metric or American cross-sections: contact us.
 - Other options and/or combinations of the options outlined above: contact us.

SILICONE INSULATED MEDIUM VOLTAGE
POWER CABLES WITH REINFORCING BRAID

- 1 • Flexible tin-plated copper core - class 5 as per IEC 60228.
- 2 • Semi-conductor tape(s).
- 3 • Insulation: Silicone rubber.
- 4 • Reinforcement: Coated synthetic fibre braid.

Characteristics**General**

- Continuous operating temperatures: -60 °C to +180 °C.
- Good resistance to thermal shock and UV.
- Excellent mechanical strength.

Electrical

- Rated voltage: 7.2 kV.
- Test voltage: 15 kV.

Standard products

- Standard insulation colour: white.
- Standard reinforcing braid colour: grey.

Style 3663 - 7.2 kV**Flexible core • class 5 as per IEC 60228**

Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)
2.5	19 × 0.40*	7.56
4	32 × 0.40*	4.70
6	48 × 0.40*	3.11
10	80 × 0.40	1.95
16	126 × 0.40	1.24
25	196 × 0.40	0.795
35	276 × 0.40	0.565
50	396 × 0.40	0.393
70	360 × 0.50	0.277
95	485 × 0.50	0.210
120	608 × 0.50	0.164
150	756 × 0.50	0.132
185	944 × 0.50	0.108
240	1221 × 0.50	0.0817
300	1525 × 0.50	0.0654
400	2037 × 0.50	0.0495

INSULATED WIRE OR CABLE

Nominal diameter (mm)	Approximate linear weight (kg/km)
7.7	69.2
8.3	89.7
9.2	119
10.4	166
11.6	227
13.1	325
14.6	425
16.7	583
18.3	759
19.9	995
23.0	1262
24.1	1555
26.9	1904
30.7	2522
32.9	3059
37.2	3999

* Tin-plated copper core – class 2 as per IEC 60228.

For this product, please contact:

OMERIN division principale 
Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.