

**SILICABLE®**  
**FHL2G**

Single core

**-40°C à +180°C****Class E according to ISO 6722-1  
and ISO 19642-1**

+180°C (3000 h)

+205°C (240 h)

**Approvals - standards\***

- ISO 19642-5, ISO 6722-1, EN 13602
- IEC 60754-1 halogen free

**Applications**

- Single core silicone power cables for use in hybrid and electrical vehicles

**Specific characteristics**

- High Voltage requirements according to ISO 19642
- Voltage rating: 1000 VAC / 1500 VDC
- Test voltage: 10 kV 5 minutes
- Sparktest: 8 kV
- Excellent flexibility
- Flame retardant
- Bending radius: 3 x D

**Colour code**

- Orange
- (others on request)



- 1 • Flexible bare copper core according to ISO 6722-1, ISO 19642-5 and EN 13602
- 2 • Silicone insulation

**CONSTRUCTION ACCORDING TO ISO 6722-1 AND ISO 19642-5**

Item code	Nominal cross section (mm <sup>2</sup> )	Number & diameter of strands nom. /max. (nb. x mm)	Conductor diameter max. (mm)	Insulation thickness min. (mm)	Cable outer diameter		Maximum linear resistance at 20°C (Ω/ km)
					max. (mm)	min. (mm)	
A2504005	0.5	16 x 0.21	1.1	0.48	2.0	2.3	37.1
A2504001	0.75	24 x 0.21	1.3	0.48	2.2	2.5	24.7
A2504002	1	32 x 0.21	1.5	0.48	2.4	2.7	18.5
A2504003	1.5	30 x 0.26	1.8	0.48	2.7	3.0	12.7
A2504004	2.5	50 x 0.26	2.2	0.56	3.3	3.6	7.60
A2503005	4	224 x 0.16	2.8	0.64	4.0	4.4	4.71
A2503006	6	320 x 0.16	3.4	0.64	4.6	5.0	3.14
A2503007	10	320 x 0.21	4.5	0.80	5.9	6.5	1.82
A2503008	16	512 x 0.21	6.3	0.80	7.7	8.3	1.16
A2503009	25	790 x 0.21	7.8	1.04	9.4	10.4	0.743
A2503010	35	1070 x 0.21	9.0	1.04	9.6	11.6	0.527
A2503002	50	1600 x 0.21	10.5	1.20	11.5	13.5	0.368
A2503004	70	2175 x 0.21	12.5	1.20	13.5	15.5	0.259
A2503011	95	3000 x 0.21	14.8	1.28	16.0	18.0	0.196
A2503012	120	3700 x 0.21	16.5	1.28	17.7	19.7	0.153

\* Standards: our products comply with all or part of the requirements of standards quoted: contact us  
Other cross-sections available on request

For this product, please contact:

OMERIN eMobility division   
9 allée des acacias - F 63190 Orléat  
Phone: +33 (0)4 73 82 75 60  
emobility@omerin.com

[www.omerin.com](http://www.omerin.com)

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In some cases, for production purposes, a separating tape may be added between two successive layers. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. © Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.