


SILICABLE®
FHLR2GCB2G LV216

Shielded single core

-40°C to +180°C**Class E according to ISO 6722-1****LV 216-2****+180°C (3000 h)****+205°C (240 h)**

- 1 • Flexible bare copper core according to ISO 6722-1 and EN 13602
- 2 • Silicone insulation
- 3 • Tinned copper braid
- 4 • Aluminium / PET tape
- 5 • Silicone sheath

**Approvals - standards***

- LV 216-2 table A.2, ISO 6722-1, EN 13602
- IEC 60754-1 halogen free

Applications

- Single core silicone power cable for use in hybrid and electrical vehicles.

Specific characteristics

- High Voltage requirements according to LV 216-2
- Voltage rating: 600 VAC / 1000 VDC
- Test voltage: 5 kV 5 minutes
- Sparktest: 8 kV
- Excellent flexibility
- Flame retardant
- Bending radius: 3 x D
- Compatible with SCHUNK Sonosystems ultrasonic welding systems

Colour code

- Orange
- (others on request)

CONSTRUCTION ACCORDING TO LV 216-2 TABLE A.2

Item code	Nominal cross section (mm ²)	Number & diameter of strands nom. /max. (nb. x mm)	Conductor diameter max. (mm)	Insulation thickness min. (mm)	Single core outer diameter (mm)		Strand diameter screen max. (mm)	Sheath thickness min. (mm)	Cable outer diameter (mm)		Maximum linear resistance at 20°C (Ω/ km)
					min.	max.			min.	max.	
A2510001	4	120 x 0.21	2.8	0.32	3.4	3.7	0.16	0.38	5.3	5.8	4.70
A2510002	6	183 x 0.21	3.4	0.32	4.0	4.3	0.16	0.46	6.0	6.5	3.10
A2510003	10	320 x 0.21	4.5	0.48	5.4	6.0	0.16	0.70	8.2	8.8	1.82
A2510004	16	512 x 0.21	5.8	0.52	6.6	7.2	0.16	0.70	9.6	10.2	1.16
A2510005	25	790 x 0.21	7.2	0.64	8.2	8.8	0.21	0.75	11.6	12.2	0.743
A2510006	35	1070 x 0.21	8.5	0.64	9.8	10.5	0.21	0.80	13.8	14.4	0.527
A2510007	50	1600 x 0.21	10.5	0.71	11.5	12.2	0.21	0.80	15.2	15.8	0.368
A2510008	70	2175 x 0.21	12.5	1.20	14.0	15.5	0.21	1.16	19.2	20.0	0.259
A2510009	95	3000 x 0.21	14.8	1.20	16.2	18.0	0.21	1.16	21.5	22.5	0.196
A2510010	120	3700 x 0.21	16.5	1.28	17.9	19.7	0.21	1.16	22.5	23.5	0.153
A2510011**	150	4560 x 0.21	17.5	1.28	20.2	22.0	0.21	1.16	24.0	26.0	0.122

* Standards: our products comply with all or part of the requirements of standards quoted: contact us

** Innovation OMERIN. Not defined in LV 216-2 Table A.2

Other cross-sections available on request

For this product, please contact:

OMERIN division principale 
Zone Industrielle - F 63600 Ambert
Phone: +33 (0)4 73 82 50 00
omerin@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In some cases, for production purposes, a separating tape may be added between two successive layers. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories. © Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.