SILICONE INSULATED AND/OR SHEATHED
WIRES AND CABLES WITH REINFORCING BRAID

SILICABLE® CSVCS and ECSVCS

Reinforced double insulating layer

-60°C to +180°C

1 • Flexible bare copper (ref. CSVCS) or tin-plated (ref. ECSVCS) core - class 5 as per IEC 60228.
2 • Insulation: Silicone rubber.
3 • Reinforcement: Fibreglass braid.

Approvals - standards

• Halogen-free: IEC 60754-1 / EN 60754-1.
• Meets the requirements of standard NF EN 60335-1: Safety of household and similar electrical appliances.

Applications

• Class 2 lighting equipment and convectors or any other household electrical appliance complying with standard NF EN 60335-1.

Options

• Nickel-plated copper core: ref. CNCSVCS.
• Silver-plated copper core: ref. ACSVCS.
• Pure nickel core (not described in IEC 60228): ref. NCSVCS.
• Solid bare copper (ref. RCSVCS) or tin-plated (ref. RECSVCS) core – class 1 as per IEC 60228: contact us.
• Extra-flexible bare copper (ref. CSVCS-ES) or tin-plated (ref. ECSVCS-ES) core – class 6 as per IEC 60228: contact us.
• Other nominal cross-sections: contact us.
• Other nominal stranding: contact us.
• Other options and/or combinations of the options outlined above: contact us.

Characteristics

General

• Continuous operating temperatures: -60°C to +180°C.
• Good resistance to thermal shock and UV.

Electrical

• Rated voltage: 300/500 V.
• Test voltage: 3750 V.

Standard products

• Inner insulating layer: white.
• Outer insulating layer: all solid colours.

CSVCS and ECSVCS

Flexible core • class 5 as per IEC 60228			INSULATED WIRE OR CABLE		
Nominal cross-section (mm²)		Maximum linear resistance at 20 °C (Ω/km) (bare copper core)	Nominal diameter (mm)		
0.5	16 x 0.20	39.0	0.9	2.8	10.9
0.75	24 x 0.20	26.0	0.9	2.9	13.0
1	32 x 0.20	19.5	0.9	3.0	15.3
1.5	30 x 0.25	13.3	1.0	3.6	22.4
2.5	50 x 0.25	7.98	1.1	4.2	33.6
4	56 x 0.30	4.95	1.2	4.9	51.1
6	84 x 0.30	3.30	1.5	6.1	77.3
10	80 x 0.40	1.91	1.7	7.8	130
16	126 x 0.40	1.21	2.0	9.4	193
25	196 x 0.40	0.780	2.2	11.4	299
35	276 x 0.40	0.554	2.4	12.8	396
50	396 x 0.40	0.386	2.6	14.8	556

For this product, please contact:

OMERIN division principale ☑
Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol ❑
BP 87 - ZI du Devey - F 42000 Saint-Étienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In some cases, for production purposes, a separating tape may be added between two successive layers. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.