

SILIFLON® ETFE and EETFE

-90 °C to +155 °C

Approvals - standards

- Series inspired by standards
NF C 93-524

Applications

- Cabling for rotating machines (class F).
- Cabling in household electrical appliances, electronics.
- Cabling in hot or cold environments (cryogenics).
- Cabling in aggressive environments (humidity, chemicals, etc.).
- Cabling requiring compact size and excellent mechanical strength.

Options

- Nickel-plated copper core: ref. CNETFE.
- Silver-plated copper core: ref. AETFE.
- Pure nickel core: ref. NETFE.
- Outer electrical shielding:
- > Tin-plated copper braid: ref. ETFEBE or EETFEBE.
- Other nominal metric or American cross-sections: contact us.
- Other nominal stranding: contact us.
- Other options and/or combinations of the options outlined above: contact us.



- 1 • Bare (ref. ETFE) or tin-plated (ref. EETFE) copper core.
- 2 • Insulation: Fluorinated polymer ETFE.

Characteristics

General

- Continuous operating temperatures: -90 °C to +155 °C.
- Excellent resistance to aggressive chemical environments.
- Excellent resistance to humidity and UV.
- Excellent mechanical strength.

Electrical

- Rated voltage: 450/750 V.
- Test voltage: 2500 V.

Standard products

- All colours including translucent.

ETFE and EETFE

CONDUCTING CORE			INSULATED WIRE OR CABLE		
Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km) (bare copper core)	Nominal thickness of insulation (mm)	Nominal diameter (mm)	Approximate linear weight (kg/km)
0.05	7 x 0.10	373	0.17	0.65	0.9
0.09	7 x 0.13	214	0.17	0.7	1.3
0.12*	7 x 0.15	161	0.17	0.8	1.7
0.14**	7 x 0.16	141	0.17	0.8	1.8
0.15	19 x 0.10	136	0.20	0.9	2.1
0.22	7 x 0.20	89.9	0.20	1.0	2.7
0.25	19 x 0.13	80.0	0.20	1.05	3.2
0.34	7 x 0.25	57.5	0.20	1.15	4.0
0.38**	19 x 0.16	54.1	0.20	1.15	4.4
0.5	7 x 0.30	39.6	0.20	1.3	5.6
0.5	16 x 0.20	39.0	0.20	1.3	5.9
0.6	19 x 0.20	32.8	0.20	1.4	6.4
0.75	24 x 0.20	26.0	0.20	1.45	8.5
0.88	7 x 0.40	22.2	0.20	1.5	9.0
0.93	19 x 0.25	21.0	0.20	1.7	10.0
1	32 x 0.20	19.5	0.20	1.7	11.4
1.34	19 x 0.30	14.6	0.20	1.9	13.9
1.5	30 x 0.25	13.3	0.20	1.95	15.6
2.5	50 x 0.25	7.98	0.20	2.5	25.6
4	56 x 0.30	4.95	0.25	3.1	38.9
6	84 x 0.30	3.30	0.35	3.9	55.6
10	80 x 0.40	1.91	0.40	5.2	101
16	126 x 0.40	1.21	0.40	6.5	147
25	196 x 0.40	0.780	0.60	8.2	242
35	276 x 0.40	0.554	0.60	9.2	320
50	396 x 0.40	0.386	0.70	11.2	465

For this product, please contact:

OMERIN division principale ✓
Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

** Nominal cross-section not available with the ref. EETFE.

** Nominal cross-sections not available with the ref. ETFE.

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.