

SILIFLON® 7Y

VDE approval
-90 °C to +135 °C



- 1 • Solid bare or tin-plated copper core.
- 2 • Insulation: Fluorinated polymer ETFE.

Approvals - standards

- VDE approval as per standard DIN VDE 0881 - licence no. 088244.

Applications

- Cabling in electronics and household appliances.
 - Cabling in hot and aggressive environments (humidity, chemicals, etc.).

Options

- Solid silver-plated copper core: contact us.
 - Twisted pair or triple or quad with no outer sheath - Standardised reference: 7Y n x Cross-section/Østranding (n being the number of twisted conductors).

Characteristics General

- Continuous operating temperatures: -90 °C to +135 °C.
- Excellent resistance to aggressive chemical environments.
- Excellent resistance to humidity and UV.
- Excellent mechanical strength.

Electrical

- Rated voltage:
 - > Nominal thickness of insulation (0.15 mm): 375 V.
 - > Nominal thickness of insulation (0.25 mm): 900 V.
- Test voltage:
 - > Nominal thickness of insulation (0.15 mm): 1500 V.
 - > Nominal thickness of insulation (0.25 mm): 2500 V.

Standard products

- All colours including translucent.

7Y

Standardised reference	SOLID CORE			INSULATED WIRE		
	Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km) (bare copper core)	Nominal thickness of insulation (mm)	Nominal diameter (mm)	Approximate linear weight (kg/km)
7Y 1 x 0.25/0.55	0.05	1 x 0.25	384	0.15	0.55	0.8
7Y 1 x 0.32/0.6*	0.08	1 x 0.32	230	0.15	0.62	1.1
7Y 1 x 0.4 /0.7	0.125	1 x 0.40	146	0.15	0.7	1.6
7Y 1 x 0.5 /0.8	0.20	1 x 0.50	93.1	0.15	0.8	2.3
7Y 1 x 0.63/0.95*	0.31	1 x 0.63	58.7	0.15	0.93	3.4
7Y 1 x 0.8 /1.1	0.50	1 x 0.80	36.0	0.15	1.1	5.3
7Y 1 x 0.25/0.75	0.05	1 x 0.25	384	0.25	0.75	1.1
7Y 1 x 0.32/0.8*	0.08	1 x 0.32	230	0.25	0.82	1.5
7Y 1 x 0.4 /0.9	0.125	1 x 0.40	146	0.25	0.9	2.0
7Y 1 x 0.5 /1.0	0.20	1 x 0.50	93.1	0.25	1.0	2.8
7Y 1 x 0.63/1.2*	0.31	1 x 0.63	58.7	0.25	1.13	4.0
7Y 1 x 0.8 /1.3	0.50	1 x 0.80	36.0	0.25	1.3	5.9
7Y 1 x 1.0 /1.5*	0.785	1 x 1.00	23.1	0.25	1.5	8.7
7Y 1 x 1.3 /1.8*	1.33	1 x 1.30	13.6	0.25	1.8	14.0
7Y 1 x 1.6 /2.1*	2.01	1 x 1.60	9.01	0.25	2.1	20.6
7Y 1 x 2.1 /2.6*	3.46	1 x 2.10	5.23	0.25	2.6	34.3

* Contact us.

For this product, please contact:

OMERIN division principale 
Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.