

SILIFLON® 6YS

VDE approval
-90 °C to +180 °C

Approvals - standards

- 6YS: VDE approval as per standard DIN VDE 0250 Part 106 - Licence no. 107583.



Applications

- Cabling in household electrical appliances, electronics.
 - Cabling in hot or cold environments (cryogenics).
 - Cabling in aggressive environments (humidity, chemicals, etc.).
- Cabling requiring compact size and excellent mechanical strength.

Characteristics

General

- Continuous operating temperatures:
 - > Bare copper core: -90 °C to +130 °C.
 - > Tin-plated, nickel-plated or silver-plated copper core: -90 °C to +180 °C.
- Excellent resistance to aggressive chemical environments.
- Excellent resistance to humidity and UV.
- Excellent mechanical strength.

Electrical 6YS

- Rated voltage: 300/500 V.
- Test voltage: 2000 V.

Standard products

- All colours including translucent.

Options

- Flexible tin-plated copper core – ref. E6YA and E6YS: contact us.
- Flexible nickel-plated copper core – ref. CN6YA and CN6YS: contact us.
- Flexible silver-plated copper core – ref. A6YA and A6YS: contact us.
- Solid bare copper core – ref. R6YA and R6YS: see details of the option below.
- Solid tin-plated copper core – ref. RE6YA and RE6YS: contact us.

6YS

Flexible core • class 5 as per IEC 60228

Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)
0.25*	19 x 0.13 or 7 x 0.22	80.7
0.5	16 x 0.20	39.0
0.6*	19 x 0.20	32.8
0.75	24 x 0.20	26.0
1	32 x 0.20	19.5
1.5	30 x 0.25	13.3
2.5	50 x 0.25	7.98
4	56 x 0.30	4.95
6	84 x 0.30	3.30

INSULATED WIRE

Nominal thickness of insulation (mm)	Nominal diameter (mm)	Approximate linear weight (kg/km)
0.30	1.25	4.2
0.30	1.5	6.5
0.30	1.5	7.4
0.30	1.65	8.7
0.30	1.8	10.9
0.30	2.0	14.9
0.35	2.6	25.0
0.40	3.4	41.9
0.40	3.9	60.1

Option • R6YS

Solid core • class 1 as per IEC 60228

0.25*	1 x 0.56	73.4	0.30	1.15	3.9
0.5	1 x 0.80	36.0	0.30	1.4	6.8
0.75	1 x 0.98	24.5	0.30	1.6	9.5
1	1 x 1.13	18.1	0.30	1.75	12.0
1.5	1 x 1.36	12.1	0.30	2.0	16.7
2.5	1 x 1.77	7.41	0.35	2.5	27.4
4	1 x 2.24	4.61	0.40	3.05	42.7
6	1 x 2.74	3.08	0.40	3.55	61.7

For this product, please contact:

OMERIN division principale
Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

* Nominal cross-sections not described in IEC 60228.

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.