

SILICABLE® GHR

Lead wire for hermetically sealed motors

-30 °C to +125 °C

UNIPOLAR WIRES AND CABLES WITH COMPOSITE INSULATION



- 1 • Flexible or extra-flexible bare copper core.
- 2 • Heat-stabilized non-coated high resistance polyester braid.
- 3 • Polyester tape(s).
- 4 • Heat-stabilized non-coated high resistance polyester braid.

Applications

- Internal cabling for hermetically sealed motors.

Options

- Other metric or American cross-sections: contact us.
- Other nominal stranding/contact us.
- Other coloured spiral stripe(s).contact us.
- Flexible or extra-flexible tinned copper core.
 - Specific insulation thickness: contact us.

Characteristics General

- Continuous operating temperature: -30°C to +125°C.
- Excellent resistance to R12, R22, R404A, R134a, R407C, R507, etc. refrigerant gases and refrigerant oils.
- Excellent mechanical strength (abrasion, vibration and alternate bending).
- Excellent chemical purity.
- Excellent resistance to aggressive chemical environments.

Electrical

- Rated voltage: 600 Vac.
- Test voltage: 3 000 Vac.

Standard products

- White with coloured spiral stripe(s): blue, red or black.

Conducting core

INSULATED WIRE OR CABLE

Nominal cross-section	Nominal stranding (flexible core)	Nominal stranding (extra-flexible core)	Max. linear resistance at 20 °C (Ω/km)	Nominal Diameter (mm)	Approximate linear weight (kg/km)
AWG (mm ²)					
- 0.75	24 x 0.20	42 x 0.15	26.0	1.9	8.6
18 -	-	65 x 0.127	21.8	1.95	9.0
- 1	32 x 0.20	-	19.5	2.1	11.0
16 -	-	105 x 0.127	13.7	2.3	14.9
14 -	-	168 x 0.127	8.62	2.9	22.7
12 -	-	259 x 0.127	5.31	3.3	33.9
- 4	56 x 0.30	-	4.95	3.8	43.0
10 -	-	13 x 0.127	3.41	4.2	54.9
- 6	-	336 x 0.15	3.30	4.1	58.0
9 -	-	378 x 0.15	2.60	4.4	65.6
8 -	-	665 x 0.127	2.15	5.2	86.9
- 10	-	784 x 0.127	1.91	5.3	110
- 16	-	504 x 0.20	1.21	6.5	161
- 25	196 x 0.40	-	0.780	8.0	252
- 35	280 x 0.40	-	0.554	9.5	348

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Étienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

OMERIN division Berne

La Forie - F 63600 Ambert
Tel. (33) 04 73 82 03 81 - Fax (33) 04 73 82 18 69
berne@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.