

SILICABLE® TEVS**-60 °C to +280 °C**UNIPOLAR WIRES AND CABLES
WITH COMPOSITE INSULATION

- 1 • Flexible bare copper core - class 5 as per IEC 60228.
- 2 • PTFE tape.
- 3 • Silicone-coated fibreglass braid.

For implementation purposes, this cable may include one or more fibreglass lappings above or below the PTFE tape.

Applications

- Cabling for heating resistors, cartridges, bands and plates.
- All cabling requiring enhanced chemical resistance.
- Cabling for domestic or professional electrical appliances.

Options

- Nickel-plated copper core: ref. CNTEVS.
- Pure nickel core (not described in IEC 60228): ref. NTEVS.
 - Fibreglass outer braid coated with PTFE varnish: ref. TEVF.
 - Silicone-coated mineral fibreglass outer braid: ref. TEVAS.
- Other nominal cross-sections: contact us.
 - Other nominal stranding: contact us.
- Other options and/or combinations of the options outlined above: contact us.

Characteristics**General**

- Continuous operating temperatures: -60 °C to +280 °C.
- Good resistance to thermal shock.
- Enhanced resistance to moisture and common chemical agents.

Electrical

- Rated voltage: 300/500 V.
- Test voltage: 2000 V.

Standard products

- All solid colours.
- All colours with coloured spiral stripe(s).

Flexible core • Class 5 as per IEC 60228

Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)
0.22*	7 x 0.20	89.9
0.34*	7 x 0.25	57.5
0.5	16 x 0.20	39.0
0.75	24 x 0.20	26.0
1	32 x 0.20	19.5
1.5	30 x 0.25	13.3
2.5	50 x 0.25	7.98
4	56 x 0.30	4.95
6	84 x 0.30	3.30
10	80 x 0.40	1.91
16	126 x 0.40	1.21
25	196 x 0.40	0.780
35	276 x 0.40	0.554
50	396 x 0.40	0.386
70	360 x 0.50	0.272
95	485 x 0.50	0.206

INSULATED WIRE OR CABLE

Nominal diameter (mm)	Approximate linear weight (kg/km)
1.3	4.5
1.7	6.7
2.1	8.7
2.4	11.9
2.5	14.3
2.8	19.1
3.2	29.3
3.8	47.4
4.4	67.5
6.2	106
7.9	192
10.0	302
12.0	395
13.4	556
16.3	785
18.0	1032

* Nominal cross-sections not described in IEC 60228.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert

Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10

omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Etienne

Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00

silisol@omerin.com

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.