



SILIFLAM® THS 1400

VERY HIGH SAFETY CABLES
FOR INDUSTRIAL APPLICATIONS

THS 1400 U



THS 1400 M

Approvals - standards

- Nickel type 200, as per standards DIN 17753, DIN 17740 and ASTM B160.

Applications

- See range presentation sheet (FT 3301).
The THS 1400 series is recommended for zones subject to very high continuous or temperature peaks (flames, falling slag, molten metals, proximity of furnace door, etc.).

Options

- Other nominal cross-sections: contact us.
- Other numbers of conductors: contact us.
- 27% nickel-plated copper conducting cores: contact us.
 - Refractory metal conducting cores: contact us.
- Other options or cables based on the THS 1400 series, designed on request: contact us.

Characteristics

General

- Continuous operating temperatures: See general presentation sheet (FT 3301).
- Good resistance to thermal shocks and ageing.

Electrical

- Rated voltage: 300/500 V to 600/1000V.
- Test voltage: THS 1400 series: 1500 V.
THS 1430 and 1450 series: 2500V.

Standard products

- See also: Range presentation sheet (FT 3301).
- Ref. THS 1400 U: Unipolar - THS 1400 type insulation.
- Ref. THS 1400 M: Multi-conductor - THS 1400 type insulation and sheathing.
- Ref. THS 1430 U/M: THS 1400 insulation / sheathing with PTFE reinforcement.
- Ref. THS 1450 U/M: THS 1400 insulation / sheathing with polyimide reinforcement.
- Ref. THS 1400 U/M - BCN: Nickel-plated copper electrical screen.
- Ref. THS 1400 U/M - BI: Stainless steel flexible armour.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Etienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

Conducting core

INSULATED CONDUCTORS

SHEATHED CABLE

Nominal cross-section (mm ²)	Nominal stranding	Maximum linear resistance at 20 °C (Ω/km)	Approximate diameter ⁽¹⁾ of single conductors (THS 1400 M version) (mm)	Approximate diameter ⁽¹⁾ of cable (THS 1400 U and THS 1400 M version) (mm)
THS 1400 U				
1 x 0.5	7 x 0.30	229	-	2.2
1 x 0.75	11 x 0.30	156	-	2.6
1 x 1	14 x 0.30	115	-	3.0
1 x 1.5	21 x 0.30	77.2	-	3.2
1 x 2.5	35 x 0.30	47.2	-	3.8
1 x 4	56 x 0.30	31.5	-	4.5
1 x 6	84 x 0.30	21.0	-	5.0
THS 1400 M				
2 x 0.5	7 x 0.30	229	2.2	6.1
3 x 0.5	7 x 0.30	229	2.2	6.4
4 x 0.5	7 x 0.30	229	2.2	6.9
5 x 0.5	7 x 0.30	229	2.2	7.7
7 x 0.5	7 x 0.30	229	2.2	8.3
2 x 0.75	11 x 0.30	156	2.6	6.8
3 x 0.75	11 x 0.30	156	2.6	7.0
4 x 0.75	11 x 0.30	156	2.6	7.7
5 x 0.75	11 x 0.30	156	2.6	8.4
7 x 0.75	11 x 0.30	156	2.6	9.1
2 x 1	14 x 0.30	115	3.0	7.7
3 x 1	14 x 0.30	115	3.0	8.2
4 x 1	14 x 0.30	115	3.0	8.9
5 x 1	14 x 0.30	115	3.0	9.8
7 x 1	14 x 0.30	115	3.0	10.6
2 x 1.5	21 x 0.30	77.2	3.2	8.0
3 x 1.5	21 x 0.30	77.2	3.2	8.5
4 x 1.5	21 x 0.30	77.2	3.2	9.2
5 x 1.5	21 x 0.30	77.2	3.2	10.2
7 x 1.5	21 x 0.30	77.2	3.2	11.2
2 x 2.5	35 x 0.30	47.2	3.8	9.1
3 x 2.5	35 x 0.30	47.2	3.8	9.6
4 x 2.5	35 x 0.30	47.2	3.8	10.7
2 x 4	56 x 0.30	31.5	4.5	10.6
3 x 4	56 x 0.30	31.5	4.5	11.2
4 x 4	56 x 0.30	31.5	4.5	12.5
2 x 6	84 x 0.30	21.0	5.0	11.6
3 x 6	84 x 0.30	21.0	5.0	12.4
4 x 6	84 x 0.30	21.0	5.0	13.7

(1) The diameters stated are approximate. They can vary substantially (± 2 mm or $\pm 20\%$) according to the series or options in question (THS 1430, THS 1450, BCN, BI option, etc.) and do not apply to derivative products designed on request, which are the subject of a specific technical data sheet.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert

Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10

omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Étienne

Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00

silisol@omerin.com

www.omerin.com

omerin
LES CABLES DE L'EXTREME

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.

For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.