

SILICABLE® RW

EN 50382-2 1800V FF 120 °C

Sheathed cable



- 1 • Flexible tin-plated copper - class 5 - EN 60228.
- 2 • Separating tape (optional).
- 3 • Silicone rubber with high mechanical properties - type EI 111 as per EN 50382-1.
- 4 • Fire resistant elastomer with high mechanical properties - type EM 106. as per EN 50382-1.

Characteristics

Thermal

Continuous operating temperature:
-40 °C to +120 °C.

Electrical

Operating voltage: 1.8 / 3 kV.
Test voltage: 6.5 kV A.C.

Mechanical

Cut-through resistance: ★★★★★
Resistance to alternate bending: ★★★★★☆
Resistance to abrasion: ★★★★★☆
Minimum static internal bending radius:
8xD.

Chemical

Acid and base resistance: ★★★★★☆
Mineral oil resistance: ★★★★★☆

Fire-smoke

Halogen-free (EN 60754-1).
Low toxicity (EN 60754-2).
Low smoke (EN 61034-2).
Flame retardant (EN 60332-1-2, EN 60332-3-24).

Options

Temperature 150 °C authorized for CuSn.

Standards and approvals

- EN 60228, EN 50382-1, EN 50382-2.
- EN 60754-1, EN 60754-2.
- EN 60332-1-2, EN 60332-3-24, EN 61034-2.

Marking

OMERIN 369- EN 50382-2 1800V 1x < cross-section > FF 120 °C - batch number - week/year

Item code	Nominal cross-section (mm ²)	Nominal stranding	Nominal insulation thickness (mm)	Nominal sheath thickness (mm)	Cable outer diameter (mm)		Maximum linear resistance at 20 °C (Ω/km)	Approx. linear weight (kg/km)
					Mini	Maxi		
A0823001	1.5	30 x 0.25	1.3	1.4	6.8	7.9	13.7	60
A0823002	2.5	50 x 0.25	1.3	1.4	7.2	8.4	8.21	75
A0823003	4	56 x 0.30	1.3	1.4	7.7	9.0	5.09	100
A0823004	6	84 x 0.30	1.3	1.4	8.2	9.6	3.39	120
A0823005	10	80 x 0.40	1.5	1.4	9.4	11	1.95	180
A0823006	16	126 x 0.40	1.5	1.4	10.5	12.2	1.24	240
A0823007	25	196 x 0.40	1.8	1.4	12.3	14.4	0.795	360
A0823008	35	276 x 0.40	1.8	1.4	13.6	15.9	0.565	460
A0823009	50	396 x 0.40	1.8	1.4	15	17.5	0.393	610
A0823010	70	360 x 0.50	1.8	1.5	16.8	19.7	0.277	830
A0823011	95	485 x 0.50	2.2	1.5	19	22.2	0.210	1100
A0823012	120	608 x 0.50	2.2	1.6	20.8	24.3	0.164	1360
A0823013	150	756 x 0.50	2.2	1.6	22.3	26.1	0.132	1660
A0823014	185	944 x 0.50	2.4	1.7	24.5	28.6	0.108	2030
A0823015	240	1221 x 0.50	2.4	1.8	27.1	31.7	0.0817	2580
A0823016	300	1525 x 0.50	2.4	1.9	29.5	34.6	0.0654	3180
A0823017	400	2037 x 0.50	2.6	2	33.2	38.9	0.0495	4180

For this product, please contact :

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Etienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.