


# ENERSYL® OS SHF1 POWER

## Multicore power cables



- 1 • Tin-plated copper core, class 2 or 5 as per IEC 60228.
- 2 • Optional separating tape.
- 3 • Insulation: cross-linked polyethylene, type XLPE + optional filler(s).
- 4 • (optional) electrical screen: aluminium/PET tape + continuity wire (EG) / tin-plated copper braid (BE) / bare copper braid (BR).
- 5 • (optional) Internal sheath: HFFR, type SHF1.
- 6 • (optional) Armour: galvanized steel braid (BG) / double steel tape (FA).
- 7 • Outer sheath: HFFR, type SHF1.

### Reference

- (example) ENERSYL® OS EG BG SHF1  
POWER 2x4 mm<sup>2</sup>  
OS: for offshore applications  
EG, BE, BR: type of electrical screen  
BG, FA: type of armour  
SHF1: nature of sheath material  
POWER: power cable  
2: number of conductors  
X, G: type of assembly without (X)  
or with (G) an earth wire  
4 mm<sup>2</sup>: cross-section in mm<sup>2</sup>

### Approvals - standards

- IEC 60228 / IEC 60092-353.  
• IEC 60092-360.
- IEC 60332-1 / IEC 60332-3.
- IEC 61034-2 / IEC 60754-1 / IEC 60754-2.

### Markings

- OMERIN – ENERSYL < OS xx xx SHF1 POWER >  
< cross-section > – 600/1000V – < batch > – < year >

### Standard products

- Sheath: grey.
- Colour identification of conductors:  
< up to 5 conductors: as per HD 308 S2.  
> more than 5 conductors: black numbered.

### Technical characteristics

#### Thermal

- Continuous operating temperature: -30 °C to +80 °C.
- Maximum core temperature: +90 °C.

#### Electrical

- Rated voltage: 600/1000 V.
- Test voltage: 3500 V.

#### Smoke - fire

- Flame retardant – cable alone: IEC 60332-1-2 / NF C 32-070 test C2.
- Flame retardant – bunched cable: IEC 60332-3-24 cat. C.
- Low smoke density: IEC 61034-2.
- Halogen-free: IEC 60754-1.
- Low corrosivity of gas emissions: IEC 60754-2.

#### Resistance of outer sheath to chemical attacks as per OMERIN test report NT140220-01:

- Good resistance to acid.
- Good resistance to base.
- Fairly good resistance to aliphatic hydrocarbons.
- Resistance to water: type AD7 as per IEC 60529 without immersion of ends.
- Resistance to UV ≥ 2000 hours as per EN 16472.

### Options

- SHF2: cross-linked HFFR outer sheath, type SHF2.
- Other colours: contact us.
- ATEX as per NF C 15-100 part 4-42 / EN 60079-14.  
Particularly suited for static facilities in potentially explosive environments, excluding the "i" intrinsic safety protection mode.  
> ENERSYL® OS BG EX SHF1 POWER: with a HFFR sheath under the armour and without hygroscopic separating tape.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert  
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10  
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devevy - F 42000 Saint-Étienne  
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00  
silisol@omerin.com

[www.omerin.com](http://www.omerin.com)

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.  
For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.  
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

NON-SHIELDED CABLES							ARMoured CABLES			
Nominal cross-section (mm <sup>2</sup> )	Nominal stranding	Nominal thickness of insulation (mm)	Nominal diameter of conductors (mm)	Nominal thickness of the sheath (mm)	Nominal outside diameter* (mm)	Approximate linear weight (kg/km)	Nominal thickness of the sheath (mm)	Nominal outside diameter* (mm)	Approximate linear weight (kg/km)	Max. linear resistance at 20 °C (Ω/km)
2 x 1.5	7 / 0.52	0.7	3.1	1.1	8.9	89	0.8	11.9	200	12.2
3 x 1.5	7 / 0.52	0.7	3.1	1.1	9.4	111	0.9	12.5	230	12.2
4 x 1.5	7 / 0.52	0.7	3.1	1.1	10.2	134	0.9	13.3	263	12.2
5 x 1.5	7 / 0.52	0.7	3.1	1.1	11.1	158	0.9	14.3	300	12.2
7 x 1.5	7 / 0.52	0.7	3.1	1.2	12.2	206	0.9	15.4	362	12.2
12 x 1.5	7 / 0.52	0.7	3.1	1.3	16.1	333	1.0	19.7	566	12.2
19 x 1.5	7 / 0.52	0.7	3.1	1.4	18.9	491	1.1	22.7	772	12.2
24 x 1.5	7 / 0.52	0.7	3.1	1.5	22.2	618	1.2	26.2	957	12.2
27 x 1.5	7 / 0.52	0.7	3.1	1.5	22.7	678	1.2	26.6	1024	12.2
37 x 1.5	7 / 0.52	0.7	3.1	1.6	25.5	897	1.2	29.7	1298	12.2
2 x 2.5	19 / 0.41	0.7	3.5	1.1	9.7	116	0.9	12.8	239	7.56
3 x 2.5	19 / 0.41	0.7	3.5	1.1	10.3	148	0.9	13.5	281	7.56
4 x 2.5	19 / 0.41	0.7	3.5	1.1	11.2	182	0.9	14.4	326	7.56
5 x 2.5	19 / 0.41	0.7	3.5	1.2	12.4	222	0.9	15.8	387	7.56
7 x 2.5	19 / 0.41	0.7	3.5	1.2	13.4	286	1.0	16.8	464	7.56
12 x 2.5	19 / 0.41	0.7	3.5	1.4	18.0	476	1.1	21.7	743	7.56
19 x 2.5	19 / 0.41	0.7	3.5	1.5	21.1	708	1.1	24.9	1020	7.56
24 x 2.5	19 / 0.41	0.7	3.5	1.6	24.8	891	1.2	28.8	1268	7.56
27 x 2.5	19 / 0.41	0.7	3.5	1.6	25.3	981	1.2	29.5	1379	7.56
37 x 2.5	19 / 0.41	0.7	3.5	1.7	28.5	1305	1.3	32.7	1751	7.56
2 x 4	56 / 0.30	0.7	4.2	1.1	11.1	154	0.9	14.3	297	5.09
3 x 4	56 / 0.30	0.7	4.2	1.2	12.0	207	0.9	15.2	361	5.09
4 x 4	56 / 0.30	0.7	4.2	1.2	13.1	258	0.9	16.5	432	5.09
5 x 4	56 / 0.30	0.7	4.2	1.2	14.2	309	1.0	17.6	497	5.09
7 x 4	56 / 0.30	0.7	4.2	1.3	15.8	415	1.0	19.4	643	5.09
12 x 4	56 / 0.30	0.7	4.2	1.4	20.9	677	1.1	24.6	986	5.09
2 x 6	84 / 0.30	0.7	4.8	1.2	12.5	206	0.9	15.9	373	3.39
3 x 6	84 / 0.30	0.7	4.8	1.2	13.3	274	0.9	16.7	450	3.39
4 x 6	84 / 0.30	0.7	4.8	1.2	14.5	345	1.0	17.9	537	3.39
5 x 6	84 / 0.30	0.7	4.8	1.3	16.2	428	1.0	19.7	661	3.39
7 x 6	84 / 0.30	0.7	4.8	1.3	17.6	564	1.0	21.4	827	3.39
2 x 10	77 / 0.40	0.7	6.0	1.2	14.9	298	1.0	18.3	494	1.95
3 x 10	77 / 0.40	0.7	6.0	1.3	16.2	416	1.0	19.7	649	1.95
4 x 10	77 / 0.40	0.7	6.0	1.3	17.7	528	1.0	21.5	792	1.95
5 x 10	77 / 0.40	0.7	6.0	1.4	19.6	650	1.1	23.4	941	1.95
2 x 16	119 / 0.40	0.7	7.2	1.3	17.6	425	1.0	21.4	688	1.24
3 x 16	119 / 0.40	0.7	7.2	1.3	18.8	585	1.0	22.5	863	1.24
4 x 16	119 / 0.40	0.7	7.2	1.4	20.8	759	1.1	24.6	1066	1.24
5 x 16	119 / 0.40	0.7	7.2	1.5	23.0	936	1.1	27.0	1287	1.24
2 x 25	192 / 0.40	0.9	9.1	1.4	21.6	644	1.1	25.6	974	0.795
3 x 25	192 / 0.40	0.9	9.1	1.5	23.3	907	1.1	27.2	1262	0.795
4 x 25	192 / 0.40	0.9	9.1	1.5	25.6	1168	1.2	29.8	1571	0.795
5 x 25	192 / 0.40	0.9	9.1	1.6	28.4	1444	1.2	32.5	1888	0.795
2 x 35	259 / 0.40	0.9	10.4	1.5	24.4	841	1.2	28.4	1213	0.565
3 x 35	259 / 0.40	0.9	10.4	1.6	26.3	1192	1.2	30.4	1605	0.565
4 x 35	259 / 0.40	0.9	10.4	1.7	29.2	1554	1.3	33.3	2010	0.565
5 x 35	259 / 0.40	0.9	10.4	1.8	32.3	1920	1.3	36.6	2440	0.565
2 x 50	370 / 0.40	1.0	12.2	1.6	28.2	1150	1.2	32.4	1591	0.393
3 x 50	370 / 0.40	1.0	12.2	1.7	30.4	1639	1.3	34.7	2129	0.393
4 x 50	370 / 0.40	1.0	12.2	1.8	33.7	2142	1.4	38.1	2684	0.393
5 x 50	370 / 0.40	1.0	12.2	1.9	37.3	2650	1.4	41.9	3267	0.393
2 x 70	333 / 0.50	1.1	14.2	1.8	32.6	1565	1.3	37.0	2090	0.277
3 x 70	333 / 0.50	1.1	14.2	1.8	34.9	2221	1.4	39.2	2781	0.277
4 x 70	333 / 0.50	1.1	14.2	2.0	39.0	2926	1.5	43.5	3569	0.277
2 x 95	444 / 0.50	1.1	16.0	1.9	36.4	2025	1.4	41.0	2628	0.210
3 x 95	444 / 0.50	1.1	16.0	2.0	39.2	2907	1.5	43.7	3554	0.210

\* The rated outer diameter of cables may vary by +/- 15% depending on the options selected.