

MULTIMAX® CI BL



Approvals - standards

- Fire retardant as per IEC 60332-3-22.
- Flame retardant as per IEC 60332-1-2.
 - Halogen free as per IEC 60754-1.
- No smoke corrosiveness as per IEC 60754-2.
 - Low smoke opacity as per IEC 61034-2.
- Manufacture and test as per IEC 60092-376 and IEC 60092-350.
 - BVM certification.

Applications

- Fixed installation on board ships.


Markings

- OMERIN 332 - MULTIMAX <CI BL or CI BL EG or CI BL EI> 150/250V <cross-section> 90C IEC 60332-3-22 <year>

Options

- FLEX series (flexible tin-plated copper core, class 5 as per IEC 60092-376 and tin-plated copper braid armour).
- Outer sheath in cross-linked HFFR compound, type SHF2 (BVM certification).

INSTRUMENTATION AND CONTROL CABLES, 150/250 V



3x0.5mm² 90C IEC 60332-3-22 2013

MULTIMAX CI BL: multi-conductor



2x0.5mm² 90C IEC 60332-3-22 2013

MULTIMAX CI BL EG: general screen



2x0.5mm² 90C IEC 60332-3-22 2013

MULTIMAX CI BL EI: individual screen

- 1 • Stranded bare copper core, class 2 as per IEC 60092-376.
- 2 • Cross-linked polyethylene insulation, type HF XLPE.
- 3 • Electrical shielding: aluminium/PET tape + continuity wire.
- 4 • Separating tape.
- 5 • Bare copper braid armour (EG and EI with continuity wire).
- 6 • Outer sheath in cross-linked HFFR compound, type SHF1.

Characteristics

- Rated voltage: 150/250 V.
- Test voltage: 1500 V.
- Continuous operating temperature: -30 °C to +80 °C.
- Maximum core temperature: +90 °C.
- Maximum core temperature in short-circuit: +250 °C.
- Minimum bending radius: 8 x D.

Standard products

- Outer sheath: grey.
- Colour identification of conductors:
 - > Multi-conductor: white numbered.
 - > Pair: blue-white numbered.
 - > Triple: blue-white-red numbered.
 - > Quad: blue-white-red-black numbered.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Étienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'ÉTRANGER

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

CORE	SHEATH			
	Nominal cross-section (mm ²)	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 0.5	6.6		65	
2 x 2 x 0.5 ⁽¹⁾	7.4	9.8	107	114
3 x 2 x 0.5	9.7	10.3	126	136
4 x 2 x 0.5	10.4	12.0	152	161
5 x 2 x 0.5	11.3	12.5	177	187
7 x 2 x 0.5	12.4	13.2	216	227
10 x 2 x 0.5	16.0	17.1	339	358
12 x 2 x 0.5	16.5	17.6	374	394
14 x 2 x 0.5	17.2	18.6	414	436
19 x 2 x 0.5	19.2	20.5	513	539
24 x 2 x 0.5	22.3	24.1	639	671
1 x 3 x 0.5	6.9		75	
2 x 3 x 0.5	10.1	10.7	132	142
3 x 3 x 0.5	10.6	11.3	161	169
7 x 3 x 0.5	13.6	14.6	315	330
12 x 3 x 0.5	18.5	19.7	486	509
1 x 4 x 0.5	7.4		87	
3 x 4 x 0.5	12.9	13.0	211	211
7 x 4 x 0.5	17.3	17.4	415	415
1 x 2 x 0.75	7.6		81	
2 x 2 x 0.75 ⁽¹⁾	8.4	11.3	141	149
3 x 2 x 0.75	11.1	12.1	168	178
4 x 2 x 0.75	13.0	13.6	201	212
5 x 2 x 0.75	13.2	14.2	236	284
7 x 2 x 0.75	15.1	17.4	328	345
10 x 2 x 0.75	18.0	19.0	456	480
12 x 2 x 0.75	19.4	21.0	507	533
14 x 2 x 0.75	20.3	22.0	564	592
19 x 2 x 0.75	22.7	24.5	707	740
24 x 2 x 0.75	26.6	28.6	884	927
1 x 3 x 0.75	7.8		96	
2 x 3 x 0.75	11.6	12.5	175	185
3 x 3 x 0.75	12.4	13.2	214	225
7 x 3 x 0.75	16.6	17.9	426	445
12 x 3 x 0.75	21.8	23.3	669	699
1 x 4 x 0.75	8.4		113	
3 x 4 x 0.75	15.7	15.8	321	321
7 x 4 x 0.75	20.4	20.5	565	565
1 x 2 x 1	7.8		92	
2 x 2 x 1 ⁽¹⁾	9.1	11.9	161	171
3 x 2 x 1	11.8	12.8	195	206
4 x 2 x 1	13.0	13.9	235	282
5 x 2 x 1	14.1	15.8	313	329
7 x 2 x 1	16.0	17.1	385	404
10 x 2 x 1	20.1	21.8	538	565
12 x 2 x 1	20.8	22.5	601	630
14 x 2 x 1	22.0	23.5	672	703
19 x 2 x 1	24.5	26.3	847	885
24 x 2 x 1	28.6	30.9	1063	1111
1 x 3 x 1	8.3		110	
2 x 3 x 1	12.5	13.3	203	213
3 x 3 x 1	13.2	14.1	251	298
7 x 3 x 1	17.7	19.1	506	527
12 x 3 x 1	23.4	25.2	802	835
1 x 4 x 1	9.1		130	
3 x 4 x 1	16.7	16.8	374	374
7 x 4 x 1	22.0	22.1	673	673

⁽¹⁾: for the EG cables: assembled as a quad.

CORE	SHEATH			
	Nominal cross-section (mm ²)	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 1.5	9.0		115	
2 x 2 x 1.5 ⁽¹⁾	10.2	13.7	205	251
3 x 2 x 1.5	13.6	15.2	286	302
4 x 2 x 1.5	15.5	16.6	345	363
5 x 2 x 1.5	16.8	18.2	406	426
7 x 2 x 1.5	18.4	21.2	505	529
10 x 2 x 1.5	23.5	25.2	711	746
12 x 2 x 1.5	24.2	26.0	799	836
14 x 2 x 1.5	25.4	27.5	898	938
19 x 2 x 1.5	28.4	30.7	1142	1190
24 x 2 x 1.5	33.4	36.1	1438	1595
1 x 3 x 1.5	9.7		139	
2 x 3 x 1.5	14.2	15.9	297	313
3 x 3 x 1.5	15.8	16.8	368	385
7 x 3 x 1.5	20.7	22.1	673	700
12 x 3 x 1.5	27.3	29.2	1081	1123
1 x 4 x 1.5	10.2		170	
3 x 4 x 1.5	19.3	19.4	486	486
7 x 4 x 1.5	25.5	25.6	900	900
2 x 0.5	6.6		65	
3 x 0.5	6.9		75	
4 x 0.5	7.4		87	
5 x 0.5	7.9		100	
7 x 0.5	8.5		120	
10 x 0.5	10.5		169	
12 x 0.5	10.8		183	
14 x 0.5	11.2		205	
19 x 0.5	12.6		250	
24 x 0.5	14.3		346	
27 x 0.5	15.3		371	
37 x 0.5	16.8		464	
2 x 0.75	7.4		81	
3 x 0.75	7.9		96	
4 x 0.75	8.4		113	
5 x 0.75	9.2		131	
7 x 0.75	9.9		159	
10 x 0.75	12.3		228	
12 x 0.75	12.5		247	
14 x 0.75	13.2		280	
19 x 0.75	15.1		380	
24 x 0.75	17.4		471	
27 x 0.75	17.9		507	
37 x 0.75	19.8		642	
2 x 1	7.8		92	
3 x 1	8.3		110	
4 x 1	9.1		130	
5 x 1	9.8		152	
7 x 1	10.5		189	
10 x 1	12.4		265	
12 x 1	13.5		326	
14 x 1	14.1		330	
19 x 1	16.2		451	
24 x 1	18.8		561	
27 x 1	19.2		606	
37 x 1	21.4		773	
2 x 1.5	8.9		115	
3 x 1.5	9.4		139	
4 x 1.5	10.2		170	
5 x 1.5	11.0		199	
7 x 1.5	12.1		247	
10 x 1.5	15.6		390	
12 x 1.5	16.1		427	
14 x 1.5	16.8		490	
19 x 1.5	18.7		601	
24 x 1.5	21.7		749	
27 x 1.5	22.1		813	
37 x 1.5	24.8		1046	