

MULTIMAX® CI 331



Approvals - standards

- Fire-resistant as per IEC 60331-1 or IEC 60331-2: 120 minutes.
- Fire retardant as per IEC 60332-3-22.
- Flame retardant as per IEC 60332-1-2.
 - Halogen free as per IEC 60754-1.
- No smoke corrosiveness as per IEC 60754-2.
 - Low smoke opacity as per IEC 61034-2.
- Manufacture and test as per IEC 60092-376 and IEC 60092-350.
 - BVM certification.

Applications

- Fixed installation on board ships.

Markings

- OMERIN 332 - MULTIMAX <CI 331 or CI 331 EG or CI 331 EI> 150/250V <cross-section> 95C IEC 60331-<1 or 2>-<120> IEC 60332-3-22 <year>

Options

- FLEX series (flexible tin-plated copper core, class 5 as per IEC 60092-376).
- Outer sheath in cross-linked HFFR compound, type SHF2.

INSTRUMENTATION AND CONTROL CABLES, 150/250 V



MULTIMAX CI 331: multi-conductor



MULTIMAX CI 331 EG: general screen



MULTIMAX CI 331 EI: individual screen

- 1 • Stranded bare copper core, class 2 as per IEC 60092-376.
- 2 • Fire-resistant elastomer insulation.
- 3 • Electrical shielding: aluminium/PET tape + continuity wire.
- 4 • Separating tape.
- 5 • Outer sheath in cross-linked HFFR compound, type SHF1.

Characteristics

- Rated voltage: 150/250 V.
- Test voltage: 1500 V.
- Continuous operating temperature: -30 °C to +80 °C.
- Maximum core temperature: +95 °C.
- Maximum core temperature in short-circuit: +250 °C.
- Minimum bending radius: 8 x D.

Standard products

- Outer sheath: orange.
- Colour identification of conductors:
 - > Multi-conductor: white numbered.
 - > Pair: blue-white numbered.
 - > Triple: blue-white-red numbered.
 - > Quad: blue-white-red-black numbered.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Etienne
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00
silisol@omerin.com

omerin
LES CABLES DE L'EXTREME

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

CORE	SHEATH			
	Nominal cross-section (mm ²)	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 0.5	6.9		46	
2 x 2 x 0.5 ⁽¹⁾	7.9	10.8	82	89
3 x 2 x 0.5	10.7	11.4	105	110
4 x 2 x 0.5	11.7	12.7	128	135
5 x 2 x 0.5	13.0	13.9	153	161
7 x 2 x 0.5	14.1	15.1	194	203
10 x 2 x 0.5	18.2	19.7	279	292
12 x 2 x 0.5	19.0	20.3	316	331
14 x 2 x 0.5	19.9	21.4	358	374
19 x 2 x 0.5	22.4	24.0	463	482
24 x 2 x 0.5	26.3	28.5	589	615
1 x 3 x 0.5	7.3		56	
2 x 3 x 0.5	11.2	11.9	109	114
3 x 3 x 0.5	11.9	12.9	138	144
7 x 3 x 0.5	16.1	17.1	265	275
12 x 3 x 0.5	21.3	22.9	437	454
1 x 4 x 0.5	7.9		68	
3 x 4 x 0.5	14.8	14.8	185	185
7 x 4 x 0.5	20.0	20.0	359	359
1 x 2 x 0.75	7.3		54	
2 x 2 x 0.75 ⁽¹⁾	8.5	11.5	100	106
3 x 2 x 0.75	11.5	12.2	127	133
4 x 2 x 0.75	12.7	13.6	157	164
5 x 2 x 0.75	13.9	14.8	188	197
7 x 2 x 0.75	15.3	16.5	242	252
10 x 2 x 0.75	19.7	21.1	348	364
12 x 2 x 0.75	20.4	22.0	397	414
14 x 2 x 0.75	21.4	23.1	452	470
19 x 2 x 0.75	24.0	26.0	587	609
24 x 2 x 0.75	28.5	30.6	748	778
1 x 3 x 0.75	7.7		67	
2 x 3 x 0.75	12.0	13.0	131	138
3 x 3 x 0.75	12.9	13.8	170	177
7 x 3 x 0.75	17.2	18.3	334	346
12 x 3 x 0.75	23.0	24.8	554	574
1 x 4 x 0.75	8.5		82	
3 x 4 x 0.75	16.2	16.2	228	228
7 x 4 x 0.75	21.5	21.5	452	452
1 x 2 x 1	7.6		62	
2 x 2 x 1 ⁽¹⁾	8.8	12.3	117	124
3 x 2 x 1	12.0	13.0	150	157
4 x 2 x 1	13.3	14.2	187	195
5 x 2 x 1	14.5	15.8	225	235
7 x 2 x 1	16.1	17.3	292	303
10 x 2 x 1	20.7	22.4	420	438
12 x 2 x 1	21.4	23.1	482	501
14 x 2 x 1	22.7	24.3	549	570
19 x 2 x 1	25.4	27.3	717	742
24 x 2 x 1	30.0	32.4	913	948
1 x 3 x 1	8.0		79	
2 x 3 x 1	12.8	13.6	155	162
3 x 3 x 1	13.6	14.4	203	211
7 x 3 x 1	18.0	19.4	406	419
12 x 3 x 1	24.2	26.1	676	699
1 x 4 x 1	8.8		97	
3 x 4 x 1	17.0	17.0	273	273
7 x 4 x 1	22.7	22.7	550	550

⁽¹⁾: for the EG cables: assembled as a quad.

CORE	SHEATH			
	Nominal cross-section (mm ²)	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 1.5	8.6		81	
2 x 2 x 1.5 ⁽¹⁾	10.1	13.8	156	164
3 x 2 x 1.5	13.8	14.7	202	211
4 x 2 x 1.5	15.4	16.5	254	265
5 x 2 x 1.5	16.8	18.0	308	320
7 x 2 x 1.5	18.6	19.9	402	417
10 x 2 x 1.5	23.8	25.8	581	605
12 x 2 x 1.5	24.8	26.7	670	695
14 x 2 x 1.5	26.1	28.2	765	793
19 x 2 x 1.5	29.3	31.7	1004	1038
24 x 2 x 1.5	34.8	37.6	1281	1328
1 x 3 x 1.5	9.1		105	
2 x 3 x 1.5	14.5	15.7	209	218
3 x 3 x 1.5	15.7	16.7	276	287
7 x 3 x 1.5	20.8	22.4	564	582
12 x 3 x 1.5	28.1	30.3	947	977
1 x 4 x 1.5	10.1		130	
3 x 4 x 1.5	19.5	19.5	374	374
7 x 4 x 1.5	26.2	26.2	766	766
2 x 0.5	6.8		46	
3 x 0.5	7.2		56	
4 x 0.5	7.8		66	
5 x 0.5	8.5		79	
7 x 0.5	9.2		100	
10 x 0.5	11.7		140	
12 x 0.5	12.1		163	
14 x 0.5	12.8		190	
19 x 0.5	14.2		235	
24 x 0.5	16.8		296	
27 x 0.5	17.1		323	
37 x 0.5	19.3		422	
2 x 0.75	7.2		53	
3 x 0.75	7.6		66	
4 x 0.75	8.2		81	
5 x 0.75	9.1		97	
7 x 0.75	10.0		124	
10 x 0.75	12.7		183	
12 x 0.75	13.1		203	
14 x 0.75	13.7		230	
19 x 0.75	15.3		296	
24 x 0.75	18.0		374	
27 x 0.75	18.4		410	
37 x 0.75	20.7		539	
2 x 1	7.4		62	
3 x 1	7.9		78	
4 x 1	8.7		96	
5 x 1	9.7		115	
7 x 1	10.5		151	
10 x 1	13.3		213	
12 x 1	13.7		244	
14 x 1	14.4		275	
19 x 1	16.3		360	
24 x 1	19.1		456	
27 x 1	19.5		500	
37 x 1	22.0		661	
2 x 1.5	8.3		81	
3 x 1.5	9.0		104	
4 x 1.5	9.8		129	
5 x 1.5	10.9		158	
7 x 1.5	11.8		205	
10 x 1.5	15.0		293	
12 x 1.5	15.4		337	
14 x 1.5	16.7		380	
19 x 1.5	18.6		501	
24 x 1.5	22.0		635	
27 x 1.5	22.5		699	
37 x 1.5	25.3		929	