

# MULTIMAX® CI BL 331



## Approvals - standards

- Fire-resistant as per IEC 60331-1 or IEC 60331-2: 120 minutes.
- Fire retardant as per IEC 60332-3-22.
- Flame retardant as per IEC 60332-1-2.
  - Halogen free as per IEC 60754-1.
- No smoke corrosiveness as per IEC 60754-2.
  - Low smoke opacity as per IEC 61034-2.
- Manufacture and test as per IEC 60092-376 and IEC 60092-350.
  - BVM certification.

## Applications

- Fixed installation on board ships.

## Markings

- OMERIN 332 - MULTIMAX <CI BL 331 or CI BL 331 EG or CI BL 331 EI> 150/250V <cross-section> 95C IEC 60331-<1 or 2>(120) IEC 60332-3-22 <year>

## Options

- FLEX series (flexible tin-plated copper core, class 5 as per IEC 60092-376 and tin-plated copper braid armour).
- Outer sheath in cross-linked HFFR compound, type SHF2.

## INSTRUMENTATION AND CONTROL CABLES, 150/250 V



MULTIMAX CI BL 331: multi-conductor



MULTIMAX CI BL 331 EG: general screen



MULTIMAX CI BL 331 EI: individual screen

- 1 • Stranded bare copper core, class 2 as per IEC 60092-376.
- 2 • Fire-resistant elastomer insulation.
- 3 • Electrical shielding: aluminium/PET tape + continuity wire.
- 4 • Separating tape.
- 5 • Bare copper braid armour (EG and EI with continuity wire).
- 6 • Outer sheath in cross-linked HFFR compound, type SHF1.

## Characteristics

- Rated voltage: 150/250 V.
- Test voltage: 1500 V.
- Continuous operating temperature: -30 °C to +80 °C.
- Maximum core temperature: +95 °C.
- Maximum core temperature in short-circuit: +250 °C.
- Minimum bending radius: 8 x D.

## Standard products

- Outer sheath: orange.
- Colour identification of conductors:
  - > Multi-conductor: white numbered.
  - > Pair: blue-white numbered.
  - > Triple: blue-white-red numbered.
  - > Quad: blue-white-red-black numbered.

For this product, please contact:

OMERIN division principale

Zone Industrielle - F 63600 Ambert  
Tel. +33 (0)4 73 82 50 00 - Fax +33 (0)4 73 82 50 10  
omerin@omerin.com

OMERIN division silisol

BP 87 - ZI du Devey - F 42000 Saint-Etienne  
Tel. +33 (0)4 77 81 36 00 - Fax +33 (0)4 77 81 37 00  
silisol@omerin.com

**omerin**  
LES CABLES DE L'EXTREME

[www.omerin.com](http://www.omerin.com)

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

© Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN.

CORE	SHEATH			
	Nominal cross-section (mm <sup>2</sup> )	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 0.5	7.6		78	
2 x 2 x 0.5 <sup>(1)</sup>	8.7	11.6	133	142
3 x 2 x 0.5	11.4	12.4	157	166
4 x 2 x 0.5	12.6	13.5	186	197
5 x 2 x 0.5	13.7	14.7	217	265
7 x 2 x 0.5	15.5	16.6	301	318
10 x 2 x 0.5	19.5	20.9	417	442
12 x 2 x 0.5	20.1	21.7	460	486
14 x 2 x 0.5	21.0	22.8	510	538
19 x 2 x 0.5	23.5	25.4	633	667
24 x 2 x 0.5	27.6	29.7	792	834
1 x 3 x 0.5	8.0		90	
2 x 3 x 0.5	11.9	12.9	164	173
3 x 3 x 0.5	12.8	13.7	197	207
7 x 3 x 0.5	17.2	18.5	386	405
12 x 3 x 0.5	22.6	24.1	600	629
1 x 4 x 0.5	8.7		105	
3 x 4 x 0.5	16.2	16.3	298	298
7 x 4 x 0.5	21.1	21.2	511	511
1 x 2 x 0.75	8.1		88	
2 x 2 x 0.75 <sup>(1)</sup>	9.3	12.5	153	163
3 x 2 x 0.75	12.4	13.2	183	194
4 x 2 x 0.75	13.5	14.4	220	266
5 x 2 x 0.75	14.6	16.3	293	310
7 x 2 x 0.75	16.5	17.7	357	376
10 x 2 x 0.75	19.2	22.5	498	526
12 x 2 x 0.75	21.7	23.2	553	583
14 x 2 x 0.75	22.1	24.5	616	648
19 x 2 x 0.75	25.3	27.4	772	810
24 x 2 x 0.75	29.6	32.0	968	1016
1 x 3 x 0.75	8.5		104	
2 x 3 x 0.75	12.9	13.8	191	202
3 x 3 x 0.75	13.6	14.6	233	280
7 x 3 x 0.75	18.5	19.7	465	486
12 x 3 x 0.75	24.3	26.0	731	764
1 x 4 x 0.75	9.4		122	
3 x 4 x 0.75	17.3	17.4	350	350
7 x 4 x 0.75	22.8	22.9	618	618
1 x 2 x 1	8.4		99	
2 x 2 x 1 <sup>(1)</sup>	9.7	13.0	174	184
3 x 2 x 1	12.9	13.8	211	256
4 x 2 x 1	14.0	15.7	289	305
5 x 2 x 1	15.9	17.0	338	356
7 x 2 x 1	17.2	19.7	416	437
10 x 2 x 1	22.0	23.6	582	613
12 x 2 x 1	22.7	24.3	650	683
14 x 2 x 1	23.8	25.7	727	762
19 x 2 x 1	26.5	28.7	917	959
24 x 2 x 1	31.3	33.8	1151	1206
1 x 3 x 1	8.8		118	
2 x 3 x 1	13.5	14.4	219	266
3 x 3 x 1	14.3	15.9	307	322
7 x 3 x 1	19.3	20.6	546	570
12 x 3 x 1	25.5	27.3	868	904
1 x 4 x 1	9.7		140	
3 x 4 x 1	18.1	18.2	404	404
7 x 4 x 1	23.8	23.9	728	728

<sup>(1)</sup>: for the EG cables: assembled as a quad.

CORE	SHEATH			
	Nominal cross-section (mm <sup>2</sup> )	Nominal outside diameter (mm)		Approximate linear weight (kg/km)
	EG	EI	EG	EI
1 x 2 x 1.5	9.5		124	
2 x 2 x 1.5 <sup>(1)</sup>	10.9	15.3	256	272
3 x 2 x 1.5	15.1	16.2	310	327
4 x 2 x 1.5	16.5	17.9	374	394
5 x 2 x 1.5	18.1	19.4	440	463
7 x 2 x 1.5	19.8	21.3	548	574
10 x 2 x 1.5	25.1	27.2	772	811
12 x 2 x 1.5	25.9	28.1	868	910
14 x 2 x 1.5	27.4	29.4	975	1020
19 x 2 x 1.5	30.6	33.1	1240	1294
24 x 2 x 1.5	36.1	39.0	1659	1736
1 x 3 x 1.5	9.9		150	
2 x 3 x 1.5	15.9	16.9	322	340
3 x 3 x 1.5	16.8	18.1	398	418
7 x 3 x 1.5	22.1	23.8	730	760
12 x 3 x 1.5	29.2	31.5	1173	1220
1 x 4 x 1.5	10.8		183	
3 x 4 x 1.5	20.8	20.9	528	528
7 x 4 x 1.5	27.5	27.9	977	977
2 x 0.5	7.7		78	
3 x 0.5	8.0		90	
4 x 0.5	8.7		105	
5 x 0.5	9.5		121	
7 x 0.5	10.2		146	
10 x 0.5	12.7		210	
12 x 0.5	13.1		224	
14 x 0.5	13.6		260	
19 x 0.5	15.7		344	
24 x 0.5	18.0		425	
27 x 0.5	18.5		455	
37 x 0.5	20.5		571	
2 x 0.75	8.1		88	
3 x 0.75	8.5		104	
4 x 0.75	9.4		122	
5 x 0.75	10.1		142	
7 x 0.75	10.8		175	
10 x 0.75	13.5		250	
12 x 0.75	13.8		280	
14 x 0.75	14.5		310	
19 x 0.75	16.7		414	
24 x 0.75	19.4		513	
27 x 0.75	19.8		552	
37 x 0.75	22.1		700	
2 x 1	8.4		99	
3 x 1	8.8		118	
4 x 1	9.7		140	
5 x 1	10.5		166	
7 x 1	11.3		204	
10 x 1	14.1		280	
12 x 1	14.5		352	
14 x 1	15.9		410	
19 x 1	17.5		487	
24 x 1	20.3		606	
27 x 1	20.7		654	
37 x 1	23.2		835	
2 x 1.5	9.5		124	
3 x 1.5	10.0		150	
4 x 1.5	10.8		183	
5 x 1.5	11.9		215	
7 x 1.5	12.9		267	
10 x 1.5	16.0		420	
12 x 1.5	16.7		463	
14 x 1.5	18.1		535	
19 x 1.5	19.9		650	
24 x 1.5	23.2		812	
27 x 1.5	23.9		880	
37 x 1.5	26.7		1133	