& DEFENCE INDUSTRIES

1 • Silver-plated copper clad-steel stranded core (CCSAg)

2 • Fluoropolymer dielectric

- 3 Silver plated copper braid
  - 4 Fluorinated polymer FEP

# Standards and approvals

#### Construction:

- UTE C 93-550
- NF C 93-550

# **KX 22A** 50 Ohms COPY THERM FOR ZOR - 58 OFMS

HIGH TEMPERATURE COAXIAL CABLES

**COAXTHERM®** 

#### **Characteristics**

• Thermal

Continuous operating temperature: -55°C to +200°C

• Chemical

Resistance to chemical environments:  $\star\star\star\star\star$ 

Resistance to humidity: ★★★★

• Fire-smoke Flame retardant

#### Marking

"COAXTHERM KX 22A - 50 Ohms - < batch number >"

#### Colour code

• Light Brown jacket For any other request: please contact us

# **Applications**

Data transmission in high temperature environment for aerospace and defence industries

# **CONSTRUCTION**

INNER CONDUCTOR (1)		DIELECTRIC (2)	OUTER CONDUCTOR (3)	OUTER SHEATH (4)	
Stranding (n x mm)	Nominal diameter (mm)	Nominal diameter (mm)	Nominal diameter (mm)	Nominal diameter (mm)	Approx. linear weight (kg / km)
7 x 0.17	0.51	1.50	2.05	2.50	15.0

### **DATA TRANSMISSION CHARACTERISTICS**

Impedance	50 Ω
Capacitance max	105 pF / m
Use frequency max	3 GHz
Velocity of propagation	69.5%
Operating voltage	1,300 V

# SIGNAL ATTENUATION

Frequency	Nominal attenuation
(MHz)	(dB / 100 m)
200	50

CGP SAS

62 route du Coin 42400 Saint-Chamond

Phone: +33 (0)4 77 31 02 54

www.omerin.com



The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company CGP SAS shall be held responsible for any incidents in the case of inappropriate uses,

particularly in the case of wiring conditions that do not respect the good practice and the standards in force.

For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

® Registered trademark of the CGP SAS. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of CGP SAS.