1 • Silver-plated copper clad-steel stranded core (CCSAg)

- 2 Fluoropolymer dielectric
- 3 Silver plated copper braid 4 • PTFE double tape
- 5 Silicone-coated fibreglass double braid

Standards and approvals

Construction:

• UTE C 93-550 / NF C 93-550

Marking

"COAXTHERM KX 25 - 75 Ohms -< batch number >"

Colour code

 Natural jacket For any other request: please contact us

Applications

Data transmission in high temperature environment for aerospace and defence industries

COAXTHERM®

KX 25 COPATHERN AS TO CHME 75 Ohms

Characteristics

• Thermal

Continuous operating temperature: -55°C to +200°C

• Chemical

Resistance to chemical environments: ★★★☆☆

• Fire-smoke

Flame retardant

CONSTRUCTION

| Inner conductor (1) | | DIELECTRIC (2) | OUTER CONDUCTOR (3) | OUTER SHEATH (4) | |
|-----------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|---------------------------------------|
| Stranding (n x mm) | Nominal diameter (mm) | Nominal diameter (mm) | Nominal diameter (mm) | Nominal diameter (mm) | Approx. linear weight (kg / km) |
| 7 x 0.235 | 0.71 | 3.70 | 4.47 | 5.90 | 71.0 |

DATA TRANSMISSION CHARACTERISTICS

| Impedance | 75 Ω |
|-------------------------|-------------|
| Capacitance max | 68.5 pF / m |
| Use frequency max | 3 GHz |
| Velocity of propagation | 69.5% |
| Operating voltage | 3,000 V |

SIGNAL ATTENUATION

| Frequency | Nominal attenuation |
|-----------|---------------------|
| (MHz) | (dB / 100 m) |
| 200 | 20 |

CGP SAS 62 route du Coin

42400 Saint-Chamond FRANCE

Phone: +33 (0)4 77 31 02 54

www.omerin.com



The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, witing and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company CGP SAS shall be held responsible for any incidents in the case of inappropriate uses,

particularly in the case of wiring conditions that do not respect the good practice and the standards in force.

For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

® Registered trademark of the CGP SAS. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of CGP SAS.