

ELECTROAIR®

EN 2267-007 DM Line Unshielded (DMA, PN, QL, RK)



1 • Nickel plated copper
or nickel plated copper alloy core

2 • Polyimide tape

3 • PTFE tape

Available twisted conductors:
by pair, triple or quad

Standards and approvals

Construction:

- EN 2267-007
- EN 2267-002
 - EN 4434

Performances:

- EN 3475
- FAR 25

Marking (ink-jet printable)

1. On customer specification

2. Inspired of EN 2084:

"TR6058 code Gauge Country
CGP NATO Code Manufacturing Year"

Colour code

- Single core – DMA: Red, Blue, Yellow, Green, White, Black, Brown, Orange, Purple, Grey
 - Two cores – PN: Blue / Red
- Three cores – QL: Blue / Red / Yellow
- Four cores – RK: Blue / Red / Yellow / Green

For any other request: please contact us

Options

Other cross-sections or constructions
on request

Applications

General-purpose airframe wires and cables
used throughout the aircraft (retro-fit):
on the flight deck, in the passenger area,
in the wings and surfaces

CGP Reference

EN 2267-007 DM Line:

EN 2267-007A (single core) = DM DMA

EN 2267-007B (two cores) = DM PN

EN 2267-007C (three cores) = DM QL

EN 2267-007D (four cores) = DM RK

CGP SAS

62 route du Coin

42400 Saint-Chamond

FRANCE

Phone: **+33 (0)4 77 31 02 54**

www.omerin.com

Characteristics

• Thermal

Continuous operating temperature: **-55°C to +260°C**

• Electrical

Operating voltage: 600 V RMS

• Mechanical

Cut-through resistance: ★★★★★☆

Resistance to abrasion: ★★★★★☆

EN 3475

• Chemical

Resistance to chemical environments: ★★★★★★

Resistance to humidity: ★★★★★★

Resistance to aircraft fluids: ★★★★★★

EN 3475

• Fire-smoke

Flame retardant

Low smoke density

EN 3475 / FAR 25

• Arc tracking resistance

EN 3475

DM DMA 1X

AWG	Stranding (n x mm)	Code EN of nominal section	Cross section (mm ²)	Cable outer diameter (mm)		Maximum linear weight (kg / km)	Maximum linear resistance at 20°C (Ω / km)
				Mini	Maxi		
26	19 x 0.10	001	0.15	0.85	0.97	2.45	160.0
24	19 x 0.12	002	0.25	0.90	1.04	3.10	114.0
22	19 x 0.15	004	0.40	1.05	1.19	4.43	60.0
20	19 x 0.20	006	0.60	1.38	1.53	7.73	33.2
18	19 x 0.25	010	1.00	1.65	1.82	11.74	21.1
16	19 x 0.30	012	1.20	2.02	2.22	16.95	14.5
14	37 x 0.25	020	2.00	2.29	2.49	22.65	10.9
12	37 x 0.32	030	3.00	2.73	2.97	33.70	6.8

DM PN 2X

DM QL 3X

DM RK 4X

AWG	Cable outer diameter (mm)		Cable outer diameter (mm)		Cable outer diameter (mm)		Maximum linear resistance at 20°C (Ω / km)
	Maxi	Maximum linear weight (kg / km)	Maxi	Maximum linear weight (kg / km)	Maxi	Maximum linear weight (kg / km)	
26	1.94	5.05	2.09	7.57	2.33	10.09	165.0
24	2.08	6.39	2.24	9.58	2.50	12.77	117.4
22	2.38	9.13	2.56	13.69	2.86	18.25	61.7
20	3.06	15.92	3.29	23.89	3.67	31.85	34.1
18	3.64	24.18	3.91	36.28	4.37	48.37	21.7
16	4.44	34.92	4.77	52.38	5.33	69.83	14.9
14	4.98	46.66	5.35	69.99	5.98	93.32	11.2
12	5.94	69.42	6.39	104.13	7.13	138.84	7.0

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company CGP SAS shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force.

For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

© Registered trademark of the CGP SAS. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of CGP SAS.