

HIFLEX® AGP 400 M

• **Conductor**

1. Class 6 red copper according to IEC 60228
2. TPE-V thermoplastic rubber

• **Control core**

3. Class 6 tin plated copper according to IEC 60228
4. Polyester elastomer
Helicoidal stranding of 3 or 4 conductors
5. Abrasion resistant polyurethan



Applications

Extra-flexible electrical cable for electrical connection between the ground and the aircraft, allowing battery charging, pre-flight provisions, checks and maintenance operations.

Marking

CGP HIFLEX AGP 400 M -
7x[*cross-section*]mm² + 6x[*nb control core*]x1 mm² - 0.6/1kV - [batch number]

Colour code

Conductor:
Blue / white (x2) / brown (x2) / black (x2)
Control core: Black numbered
External Sheath: Orange
Other: please consult us.

General characteristics

• **Thermal**

Maximal use temperature in static use: **-40°C to +90°C**
Maximal use temperature in dynamic use: **-20°C to +90°C**

• **Electrical**

Operating voltage: 0.6 / 1 kV
Nominal voltage: 115 / 230 V
Test voltage: 4000 V
Maximal current rating : 25mm² : 210A / 35mm² : 270A
(*Tambient: 30°C / Tconductor: 90°C*)


• **Mechanical strength**

Minimal bending radius : 4 x Ø in static use
6 x Ø in dynamic use

Resistance to torsion and flexion: ★★★★★☆
Resistance to abrasion and tear: ★★★★★

• **Chemical**

All materials comply with the RoHs and Reach european directives
Good resistance to ozone, water, UV radiations and mineral oils
Halogen free materials according to IEC 60754
No corrosive and low toxicity gases.



7x25 mm² + 6x4x1 mm²
7x35 mm² + 6x4x1 mm²

Also available in
7x25 mm² + 6x3x1 mm²
7x35 mm² + 6x3x1 mm²

*General assembling: Helicoidal stranding
Assembling protection by non woven polyester tape (covering : 25% min).*

AGP 400 M

Nb cores x Cross section	Cable outer diameter (mm)		Voltage drop (mV/Am)	Maximum linear resistance at 20°C (Ω / km)	Approx. Cable weight (kg / m)
	Min	Max			
7x25 mm ² + 6x3x1 mm ²	35.5	38.5	1 mm ² : 49 25mm ² : 1.85	1 mm ² : 20.5 25 mm ² : 0.84	2.5
7x25 mm ² + 6x4x1 mm ²	35.5	38.5	1 mm ² : 49 25mm ² : 1.85	1 mm ² : 20.5 25 mm ² : 0.84	2.5
7x35 mm ² + 6x3x1 mm ²	37.5	40.5	1 mm ² : 49 35 mm ² : 1.3	1 mm ² : 20.5 35 mm ² : 0.60	3.2
7x35 mm ² + 6x4x1 mm ²	37.5	40.5	1 mm ² : 49 35 mm ² : 1.3	1 mm ² : 20.5 35 mm ² : 0.60	3.2

For this product, please contact:

CGP SAS

62 route du Coin - 42400 Saint-Chamond - FRANCE
Phone: **+33 (0)4 77 31 02 54**
www.cgp@omerin.com



www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company CGP SAS shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.

© Registered trademark of the CGP SAS. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of CGP SAS.