MOBILE APPLICATIONS

HIFLEX® AGP 400 M

Single core

- **Conductor**

1. Class 6 red copper according to IEC 60228

- **Control core**

2. Class 6 tin plated copper according to IEC 60228

3. Thermoplastic

4. Abrasion resistant polyurethan



Applications

400 Hz extra-flexible electrical cable for mobile applications : connection between the ground and the aircraft, allowing battery charging, pre-flight provisions, checks and maintenance operations.

Marking

CGP HIFLEX AGP 400 M - [cross-section]mm² - 0.6/1kV – [batch number]

Colour code

Conductor: Yellow, Green, Red, Black
Inner Sheath : Orange (abrasion indicator)
External Sheath : Black
Other: please consult us.

General characteristics

- **Thermal**

Maximal use temperature in static use: **-40°C to +90°C**
Maximal use temperature in dynamic use: **-20°C to +90°C**

- **Electrical**


Operating voltage: 0.6 / 1 kV
Test voltage: 4000 V

- **Mechanical strength**

Minimal bending radius : 4 x Ø in static use
6 x Ø in dynamic use
Resistance to torsion and flexion: ★★★★☆
Resistance to abrasion and tear: ★★★★★

- **Chemical**

All materials comply with the RoHs and Reach european directives
Good resistance to ozone, water, UV radiations and mineral oils
Halogen free materials according to IEC 60754
No corrosive and low toxicity gases.



70 mm²

General assembling: Helicoïdal stranding
Assembling protection by non woven polyester tape (covering : 25% min).

AGP 400 M

Nb cores x Cross section	Cable outer diameter (mm) Min	Cable outer diameter (mm) Max	Voltage drop (mV/Am)*	Maximum linear resistance at 20°C (Ω / km)	Maximal current rating per phase (A) *2	Approx. Cable weight (kg / m)
70 mm²	15.6	17.2	70 mm²: 0.46	70 mm²: 0.277	280	0.8

** Voltage drop between phase and neutral*
For cos Φ = 0.8
Temperature = 20 degrees Celsius

**2 : (Tambient: 30°C / Tconductor: 90°C)*

For this product, please contact:
CGP SAS
62 route du Coin - 42400 Saint-Chamond - FRANCE
Phone: **+33 (0)4 77 31 02 54**
www.cgp@omerin.com

www.omerin.com

The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company CGP SAS shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.
® Registered trademark of the CGP SAS. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of CGP SAS.