

POWER CONNECT®

HIGH-PERFORMANCE POWER CORDS



**CUTTING EDGE TECHNOLOGY
HIGH PERFORMANCE
SAVES TIME AND CONTROL
CUSTOMISED SOLUTION**

POWER CONNECT®

*A range of power cords
fitted with crimped lugs
in line with your needs.
Discover the efficiency of
SILICOUL®, **VARPREN®** and
PLASTHERM® cables supplied
at the desired length.*



POWER CONNECT®

HIGH-PERFORMANCE POWER CORDS

TECHNICAL EXPERTISE

The **POWER CONNECT®** range springs from the know-how and technical expertise of our engineers. Based on the **SILICOUL®**, **VARPREN®** and **PLASTHERM®** power cables, our technical teams make up leads fitted with crimped lugs and delivered at the length specified by our customers.

Our Design Office is made up of experienced engineers who are specialists in metallurgy, plastics manufacture, electromagnetic compatibility, micromechanics, data transmission, etc. It will provide you with a fast, precise response by developing a **POWER CONNECT®** solution in line with the miscellaneous and complex constraints of your applications.

HIGH PERFORMANCE

Cables are crimped and cut in our workshops to ensure optimum mechanical and electrical resistance in line with our customers' specifications. We thus offer a full, tested (voltage drop, tensile strength, etc.), ready-to-use solution.

APPROPRIATE CONNECTORS

Our engineers select the most appropriate power lugs for your application and the use environment of your product.

Shape: Tubular, elbowed, angled, other designs possible

Material: Metallic (tinned electrolytic copper, aluminium, etc.)

Crimping: Manual or hydraulic press

✓ **Contact us to define with our sales engineers the product best suited to your application.**

CHARACTERISTICS	PLASTHERM® CONNECT	SILICOUL® CONNECT	VARPREN® 155 CONNECT
Operating temperature	-20°C to +80°C	-60°C to +180°C Good thermal shock resistance	-50°C to +155°C
Operating voltage	Low and medium voltage (contact us)	1.1 kV to 13.8 kV	1 000 V
Mechanical behaviour	Excellent abrasion resistance	Good mechanical strength	Excellent tearing strength
Outside use	Optional	Good UV resistance	-
Halogen-free	Optional	Yes	Yes
Fire performance	Optional: Flame retardant Fire retardant	Flame retardant	Flame retardant Fire retardant Low smoke emission

SAMPLE CONFIGURATIONS

**PLASTHERM® 830 MM²
CONNECT-CT4 L = 1.50 M**



**SILICOUL® 1.1 KV 240 MM²
CONNECT-CT2 L = 2.00 M**



**VARPREN® 155 70 MM²
CONNECT-90CT1 L = 2.50 M**



CGP SAS
62 route du coin - 42400 Saint-Chamond - FRANCE
Phone: +33 (0)4 77 31 02 54 Fax: +33 (0)4 77 31 02 35
www.omerin.com

www.omerin.com