

COPPER TUBES WITH REINFORCING SHEATH

REINFORCED TUBES

BITUBE® CRP 2 TUBOL® CRP with PVC sheath



Description

2 TUBOL® CRP, flat polyvinyl chloride sheath

Applications

Pressurised transport of compressed air, lubricant

Fields

Maintenance, control, process, instrumentation

General characteristics

- Very good resistance to pressure
- External mechanical and chemical resistance

Technical data

- Temperature of use: **-20°C to +90°C**
 - Sheath: PLASTUB® GR black - Non flame-propagating PVC type C2 as per NF C 32070
- Recommended connection: bicone ring connector

Options (contact us)

- Other sheath colours
- Other qualities of external sheaths

Nominal internal diameter (mm)	Nominal outside diameter (mm)	Form of sheath	Thickness of sheath (mm)	Operating pressure* (bar)	Burst pressure* (bar)	Nominal linear weight (g/m)
4	6	Flat cable	1	220	660	410
6	8	Flat cable	1	145	435	560
8	10	Flat cable	1	110	330	750

Nominal internal diameter (mm)	Standard packaging	
	Roll (m)	Drum
4	50	On request
6	50	On request
8	50	On request

Standard tolerances: refer to pages 115 to 118.

*Values provided for information purposes for an ambient temperature of 23°C.



Zone Industrielle 63600 AMBERT - France
Tel. + 33 (0)4 73 82 44 36
e-mail: plastub@omerin.com

www.plastub.fr

The information given in this technical data sheet is indicative and subject to change without prior notice. As the conditions of use and the environment in which the product is used cannot be fully covered in our design work, PLASTUB shall not assume liability for any incidents in the event of inappropriate use and/or not carried out according to best practices and applicable standards.

To ensure optimal use of our products, we recommend full tests in real-life situations.

To this end, our sales department is on hand to supply samples and/or to examine the conditions of comprehensive testing in our laboratories.

© Registered trademark of PLASTUB. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of PLASTUB.