THERMOPLASTIC EXTRUDED TUBES

TUBES

PLASTUB® PVC29 BUL

PVC bulb tube 68 Shore A Food grade crystal



Polyvinyl chloride extruded bulb tube

Unpressurised transport of air, fluids

• Standard: Material suitable for food contact under certain conditions • Standard interval: 1 m

• Temperature of use: -30°C to +50°C • Nominal hardness: **68 Shore A**

• Nominal density: 1.20 as per ISO 1183

• Tensile strength: >17 Mpa

• Elongation at break: >280 %

Description

Applications

Fields

with variable diameter

Oxygen therapy, laboratory **General characteristics** • Flexible, economic, versatile • Used to connect two elements with

> different cross sections • Good resistance to acids, bases and detergents • Recyclable

> > **Technical data**

as per ISO R 868

as per ISO R 527

as per ISO R 527 • Standard colour: crystal • Recommended connection: nipple with lug clamp or band clamp

> Options (contact us) • Other diameters • Other solid colours

Tube Nominal internal diameter x nominal outside diameter	Bulb Nominal internal diameter x nominal outside diameter	Nominal thickness	Nominal linear weight	Standard packaging Roll
(mm)	(mm)	(mm)	(g/m)	(m)
3 x 5	6 x 10.5	1	42	50
4 x 5	10 x 12.5	0,5	31	50
4 x 6	8 x 11	1	36	50
4 x 7	7 x 12	1,5	56	50
5 x 7.5	8 x 12	1,75	52	50
5.5 x 8	8 x 11.5	1,75	48	50
7 x 9	9 x 11.5	1	39	50
7 x 10	10 x 15	1,5	83	50

Standard tolerances: refer to pages 115 to 118.

Variant

PLASTUB® 24 BUL PVC bulb tube 84 Shore A Food grade crystal



• Other packaging • Surface marking • Additives: Anti-UV, antibacterial etc.



Zone Industrielle 63600 AMBERT - France Tel. + 33 (0)4 **73 82 44 36** e-mail: *plastub@omerin.com*

www.plastub.fr

The information given in this technical data sheet is indicative and subject to change without prior notice. As the conditions of use and the environment in which the product is used cannot be fully covered in our design work, PLASTUB shall not assume liability for any incidents in the event of inappropriate use and/or not carried out according to best practices and applicable standards. To ensure optimal use of our products, we recommend full tests in real-life situations. To this end, our sales department is on hand to supply samples and/or to examine the conditions of comprehensive testing in our laboratories.

© Registered trademark of PLASTUB. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of PLASTUB.