FORMED ALUMINIUM FOIL TUBES WITH REINFORCING SHEATH

TUBOL® ALU Aluminium tape

with PE sheath



Description

Pre-formed aluminium tape with high-density polyethylene sheath

Applications

Pressurised transport of compressed air, lubricant

Fields

Maintenance, control, process, instrumentation

General characteristics

• Tool-free cold forming • Small bending radius • Good resistance to atmospheric conditions, hydrocarbons, lubricants and solvents

Technical data

• Temperature of use: -40°C to +80°C • Sheath: PLASTUB® PEHD black • Recommended connection: compression tube fittings

> **Options** (contact us) • Other diameters

Nominal internal diameter	Nominal outside diameter	Bending radius*	Operating pressure*	Burst pressure*	Nominal linear weight
(mm)	(mm)	(mm)	(bar)	(bar)	(g/m)
3,1	6	25	40	120	25
5,1	8	42	33	100	42
6,3	10	45	40	115	57
6,9	10	48	26	80	48
8,13	12	66	30	98	75
8,9	12	70	20	60	64
9,75	14	82	30	98	96
10,8	15	86	20	65	106
10,9	14	90	12	40	79

Nominal internal diameter	Standard packaging Roll Drum		Markings	
(mm)	(m)		(white)	
3,1	100	On request	TUBOL [®] ALU 3.1X6 + BATCH No.	
5,1	100	On request	TUBOL [®] ALU 5.1X8 + BATCH No.	
6,3	100	On request	TUBOL [®] ALU 6.3X10 + BATCH No.	
6,9	100	On request	TUBOL [®] ALU 6.9X10 + BATCH No.	
8,13	100	On request	TUBOL [®] ALU 8.13X12 + BATCH No.	
8,9	100	On request	TUBOL [®] ALU 8.9X12 + BATCH No.	
9,75	100	On request	TUBOL [®] ALU 9.75X14 + BATCH No.	
10,8	100	On request	TUBOL [®] ALU 10.8X15 + BATCH No.	
10,9	100	On request	TUBOL [®] ALU 10.9X14 + BATCH No.	

Standard tolerances: refer to pages 115 to 118.

*Values provided for information purposes for an ambient temperature of 23°C.



Zone Industrielle 63600 AMBERT - France Tel. + 33 (0)4 73 82 44 36 e-mail: plastub@omerin.com

www.plastub.fr

The information given in this technical data sheet is indicative and subject to change without prior notice. As the conditions of use and the environment in which the product is used cannot be fully covered in our design work, PLASTUB shall not assume liability for any incidents in the event of inappropriate use and/or not carried out according to best practices and applicable standards.

process and approach standards. To ensure optimal use of our products, we recommend full tests in real-life situations. To this end, our sales department is on hand to supply samples and/or to examine the conditions of comprehensive testing in our laboratories. Registered trademark of PLASTUB. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of PLASTUB.