



PLASTHERM® 80°C

PVC multiconductor cables

- Operating temp. -30°C to +80°C
- 300 V / 600 V / 1,000 V
- Good chemical resistance

17

Construction

- 1 - Stranded or solid tin plated or bare copper conductor (other material available on request)
 - 2 - Extruded PVC insulation
 - 3 - Extruded PVC outer jacket
- Optional shield:** consult us

Approvals - standards

- Compliance UL/cUL file E93624
- RoHS Compliant



Use: External or internal wiring of appliances

Standard products

Color coding = Insulated singles as per NEC NFPA 70
Outer jacket standard color: Black or White
Surface marking

Voltage		300 V		600 V or 1,000 V	
UL		2464		2570	
cUL		-		AWM II A/B	
Nb of Singles	AWG Size	Nominal OD (in)	Approx. linear weight (lbs/mft)	Nominal OD (in)	Approx. linear weight (lbs/mft)
2	26	.158	12.1	.224	22.4
3	26	.165	14.0	.240	26.4
4	26	.177	16.3	.260	30.7
5	26	.193	19.2	.284	35.8
2	24	.169	14.4	.232	24.6
3	24	.177	16.8	.248	29.1
4	24	.193	20.3	.268	34.0
5	24	.209	23.7	.295	40.5
2	22	.177	17.3	.240	27.9
3	22	.189	21.3	.256	33.3
4	22	.201	25.0	.280	40.1
5	22	.221	30.1	.303	46.6
2	20	.197	23.4	.264	35.7
3	20	.209	29.1	.280	43.1
4	20	.224	35.2	.307	52.7
5	20	.244	42.0	.335	62.0
2	18	.217	31.0	.280	43.5
3	18	.228	39.1	.299	54.2
4	18	.248	48.4	.327	66.3
5	18	.278	58.4	.358	79.2
Flame ratings		Cable flame		Cable flame / FT1	

Other number of singles and AWG sizes on request

Other style nos. available: please consult our complete list of UL approved styles (pages 92 to 96)

Further information concerning conducting metal: please consult our complete list of UL approved styles (pages 92 to 96)

■ UL approved only



OMERIN USA, Inc. QS Technologies division
95 Research Parkway, Meriden,
Connecticut 06450
Phone: 203-237-2297
qstech@omerin.com

www.omerin.com

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.