



PLASTHERM® 90°C

PVC multiconductor cables

- Operating temp. -30°C to +90°C
- 300 V / 600 V
- Good chemical resistance

18

Construction

- 1 - Stranded or solid tin plated or bare copper conductor (other material available on request)
 - 2 - Extruded PVC insulation
 - 3 - Extruded PVC outer jacket
- Optional shield:** consult us

Approvals - standards

- Compliance UL/cUL file E93624
- RoHS Compliant



Use: External or internal wiring of appliances

Standard products

Color coding = Insulated singles as per NEC NFPA 70
Outer jacket standard color: Black or White
Surface marking

Voltage		300 V		600 V or 1,000 V	
UL		2464		2587	
cUL		-		AWM II A/B	
Nb of Singles	AWG Size	Nominal OD (in)	Approx. linear weight (lbs/mft)	Nominal OD (in)	Approx. linear weight (lbs/mft)
2	26	.154	11.6	.224	22.4
3	26	.161	13.5	.240	26.4
4	26	.173	15.8	.260	30.7
5	26	.189	18.7	.284	35.8
2	24	.169	14.4	.232	24.6
3	24	.177	16.8	.248	29.1
4	24	.193	20.3	.268	34.0
5	24	.209	23.7	.295	40.5
2	22	.185	18.5	.240	27.9
3	22	.197	22.5	.256	33.3
4	22	.213	27.0	.280	40.1
5	22	.228	31.4	.303	46.6
2	20	.201	24.0	.264	35.7
3	20	.213	29.8	.280	43.1
4	20	.232	36.7	.307	52.7
5	20	.252	43.6	.335	62.0
2	18	.221	31.7	.280	43.5
3	18	.232	39.8	.299	54.2
4	18	.256	50.0	.327	66.3
5	18	.280	60.1	.358	79.2
Flame ratings		Cable flame		Cable flame / FT1	

Other number of singles and AWG sizes on request

Other style nos. available: please consult our complete list of UL approved styles (pages 92 to 96)

)Further information concerning conducting metal: please consult our complete list of UL approved styles (pages 92 to 96)

■ UL approved only



OMERIN USA, Inc. QS Technologies division
95 Research Parkway, Meriden,
Connecticut 06450
Phone: 203-237-2297
qstech@omerin.com

www.omerin.com

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.