



SILIFLON® 250°C
 Wrapped PTFE insulated wires

- Operating temp. -90°C to +250°C
- 300 V / 600 V
- Excellent chemical resistance
- Excellent mechanical strength
- Miniature size & lightweight

Construction

- 1 - Stranded nickel plated copper conductor
- 2 - Wrapped and sintered PTFE tape(s)

Approvals - standards

- Compliance UL/cUL file E93624
- RoHS Compliant



Use: Internal wiring of appliances or electronic equipment

Standard products
 Color coding = single color
 Surface marking

Voltage		600 V	
UL		10506	
cUL		AWM I A/B	
AWG Size	Nominal OD (in)	Approx. linear weight (lbs/mft)	
30	.026	1.0	
28	.030	1.5	
26	.034	2.1	
24	.039	2.9	
22	.046	4.6	
20	.054	7.5	
18	.067	11.9	
16	.077	16.9	
14	.092	27.6	
12	.117	42.9	
Flame ratings		Horizontal / FT1, FT2	

Other AWG sizes on request

Other style nos. available: please consult our complete list of UL approved styles (pages 92 to 96)

Further information concerning conducting metal: please consult our complete list of UL approved styles (pages 92 to 96)

UL approved only



OMERIN USA, Inc. QS Technologies division
 95 Research Parkway, Meriden,
 Connecticut 06450
 Phone: 203-237-2297
 qstech@omerin.com

www.omerin.com

* Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.