

**SILIFLON® 200°C**  
 Fiberglass braided fluoropolymer  
 insulated wires

- Operating temp. -90°C to +200°C
- 300 V / 600 V
- Excellent chemical resistance
- Excellent mechanical strength

**Construction**

- 1 - Stranded or solid tin, silver, nickel plated or bare copper conductor (tin plated or bare copper strands > .015 in)
- 2 - Extruded FEP insulation
- 3 - Lacquered fiberglass braid

**Approvals - standards**

- Compliance UL/cUL file E101965
- RoHS Compliant



Use: Internal wiring of appliances, hermetically sealed motors

**Standard products**

Color coding = single color, or color stripes  
 Marking on the extruded layer

Voltage	600 V			
Conductor	SOLID		STRANDED	
UL	11881			
cUL	AWM I A/B			
AWG Size	Nominal OD (in)	Approx. linear weight (lbs/mft)	Nominal OD (in)	Approx. linear weight (lbs/mft)
24	.045	3.1	.047	3.2
22	.047	4.5	.051	4.8
20	.057	7.5	.063	7.9
18	.063	11.2	.069	11.7
16	.079	16.6	.087	17.4
14	.091	27.1	.098	28.0
12	-	-	.126	43.4
10	-	-	.154	65.8
8	-	-	.205	114
6	-	-	.268	185
4	-	-	.319	313
2	-	-	.382	481
1	-	-	.445	661
1/0	-	-	.488	820
2/0	-	-	.532	1,024
3/0	-	-	.595	1,266
4/0	-	-	.658	1,550
Flame ratings	Horizontal / FT1, FT2			

Other AWG sizes on request

Other style nos. available: please consult our complete list of UL approved styles (pages 92 to 96)

Further information concerning conducting metal: please consult our complete list of UL approved styles (pages 92 to 96)

UL approved only



OMERIN USA, Inc. QS Technologies division  
 95 Research Parkway, Meriden,  
 Connecticut 06450  
 Phone: 203-237-2297  
 qstech@omerin.com

[www.omerin.com](http://www.omerin.com)

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.