



ELECTROAIR® M6BA-A6

FEP jacket and insulation
Silver plated copper braid

66

- Operating temp. -90°C to +200°C
- 600 V
- Excellent mechanical strength
- Excellent chemical resistance

Construction

- 1- Silver plated copper conductor
- 2- Fluoropolymer FEP insulation
- 3- Silver plated copper braid
- 4- Fluoropolymer FEP jacket

Approvals - standards

- Construction based on MIL W and NEMA standards
- Flame ratings FAR 25
- RoHS Compliant



Use: aeronautical and electronic applications and all instrumentation uses requiring excellent resistance to high temperatures and to chemical influences

Standard products

Color coding = according to ICEA Method 1 Table E-1

Options

- 250 V rating voltage – please contact us
- Unshielded version – please contact us

Nb of Singles	AWG Size	Nominal stranding (Nb x AWG)	Nominal OD (in)	Max DC Resistance at 20°C (Ω/mft)	Approx. linear weight (lbs/mft)
2x	26	19 x 38	.115	38.4	12.3
3x	26	19 x 38	.125	38.4	15.0
4x	26	19 x 38	.137	38.4	18.0
2x	24	19 x 36	.123	24.3	14.3
3x	24	19 x 36	.141	24.3	18.6
4x	24	19 x 36	.152	24.3	22.0
2x	22	19 x 34	.136	15.1	17.6
3x	22	19 x 34	.150	15.1	22.4
4x	22	19 x 34	.170	15.1	27.8
2x	20	19 x 32	.147	9.2	21.8
3x	20	19 x 32	.178	9.2	29.8
4x	20	19 x 32	.190	9.2	35.8
2x	18	19 x 30	.170	5.8	29.6
3x	18	19 x 30	.185	5.8	38.3
4x	18	19 x 30	.215	5.8	48.8

Other number of singles and AWG sizes on request



OMERIN USA, Inc. QS Technologies division
95 Research Parkway, Meriden,
Connecticut 06450
Phone: 203-237-2297
qstech@omerin.com

www.omerin.com

® Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.