

SILIGAINÉ® 13F4
Polyurethane varnish
coated fiberglass sleeving

- **Class F / +155°C (311°F)**
- **Dielectric grade: 4,000 V**
- **Very good flexibility**
- **Halogen-free**

Construction

Polyurethane coated fiberglass sleeving

Approvals - standards

- Compliance UL file E310331 category UZKX2
- RoHS Compliant



Use: Internal cabling for rotating and static machines, jacketing of cable harnesses. All insulations classes B and F

Standard products

Color: Natural

Supply: Continuous spooled lengths or cut lengths

Inner diameter (mm)	Closest Trade size (*) AWG	Inner diameter (in)	Approx. thickness (in)	Weight (lbs/mft)
0.5	24	.020	.0098	1.1
0.8	22	.031	.0098	1.7
1	19	.039	.0098	2.2
1.5	15	.059	.0138	3.4
2	13	.079	.0138	4.5
2.5	11	.098	.0157	5.8
3	9	.118	.0157	7.0
3.5	8	.138	.0157	8.3
4	7	.157	.0197	9.5
4.5	6	.177	.0197	10.9
5	5	.197	.0197	12.3
6	3	.236	.0197	15.1
7	2	.276	.0197	18.1
8	1-0	.315	.0197	21.2
10		3/8 in	.0256	27.7
12		7/16 in - 1/2 in	.0256	34.7
14		1/2 in - 5/8 in	.0256	42.3
16		5/8 in	.0256	50.3
18		11/16 in	.0256	58.9
20		1/2 in - 5/8 in	.0256	67.9
22		5/8 in	.0256	78.0
25		11/16 in	.0256	84.0
Flame ratings	Horizontal			

(*) other trade sizes on request



OMERIN USA, Inc. QS Technologies division
95 Research Parkway, Meriden,
Connecticut 06450
Phone: 203-237-2297
qstech@omerin.com

www.omerin.com

* Registered trademark of the OMERIN Group. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of OMERIN. The information provided in this technical data sheet is indicative and may be modified without prior notice, laying, wiring and electrical conditions and the environment of the cable can not be fully considered in our studies. In no way the company OMERIN shall be held responsible for any incidents in the case of inappropriate uses, particularly in the case of wiring conditions that do not respect the good practice and the standards in force. For an optimum use of the cables produced by our company, we recommend testing in real conditions. Our sales department is available for a possible provision of samples, and/or for the conditions of a complete study in our laboratories.